

Catalogue No: **1756-OB32**
CONTROLLOGIX 32DO 10-31V DC MODULE

Automation Systems > Modular Programmable Controllers > Large PLC Systems > Allen-Bradley ControlLogix® > ControlLogix® I/O Modules > ControlLogix® Digital I/O Modules



10-31 V DC Output 32 Pts (36 Pin)



- Variety of voltages
- 8 to 32 points per module
- Isolated and nonisolated module types
- Point-level output fault states
- Direct-connect or rack-optimized communication
- Field-side diagnostics on select modules

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	ControlLogix (Bul. 1756 / 1757)
Component Type PLC & I/O	Digital Output Module
Number of Digital Outputs	32 qty
Digital Output Type	12/24V DC Sourcing type
Digital Output Range	10 ... 31.2V DC
Rated Current per Digital Output, Max	0.35 A max, per DO
Rated Current per Module, Max	10 A max, per module
Module Specific Functions	ControlLogix DC (10...31.2V) output module, 32 (16 points/group)
Operating Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Vibration Acceleration (Max.)	2 m/s²
Vibration Frequency, Operational (Max.)	500 Hz
Standards Compliance	IEC 60068-2-1 IEC 60068-2-14 IEC 60068-2-2 IEC 60068-2-27 IEC 60068-2-30 IEC 60068-2-6 IEC 61000-4-2 IEC 61000-4-3 IEC 61000-4-4 IEC 61000-4-5 IEC 61000-4-6 IEC 61000-6-4

Catalogue No: **1756-OB32**
CONTROLLOGIX 32DO 10-31V DC MODULE

Automation Systems > Modular Programmable Controllers > Large PLC Systems > Allen-Bradley ControlLogix® > ControlLogix® I/O Modules > ControlLogix® Digital I/O Modules



Certifications	ATEX CE CSA C-Tick FM KC (KCC) UL
----------------	---

REFERENCES	
IECEEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-