

SIMATIC S7-400, CPU 416-3 Central processing unit with: Work memory 5.6 MB, (2.8 MB code, 2.8 MB data), 1st interface MPI/DP 12 Mbit/s, 2nd interface PROFIBUS DP, 3rd interface plug-in IFM module

General information	
Product type designation	CPU 416-3
Firmware version	V4.0
Engineering with	
• Programming package	STEP 7 V5.2 SP1 HF3 or higher with HW update
CiR – Configuration in RUN	
CiR synchronization time, basic load	100 ms
CiR synchronization time, time per I/O byte	40 μs
Supply voltage	
Rated value (DC)	Yes
• 24 V DC	
Input current	
from backplane bus 5 V DC, typ.	1.2 A
from backplane bus 5 V DC, max.	1.4 A
from backplane bus 24 V DC, max.	Total current consumption of the components connected to the MPI/DP interfaces, but no more than 150 mA per interface
Power loss	
Power loss, typ.	5 W
Memory	
Work memory	
• integrated (for program)	2 800 kbyte
• integrated (for data)	2 800 kbyte
• expandable	No
Load memory	
• expandable FEPRM	Yes; with Memory Card (FLASH)
• expandable FEPRM, max.	64 Mbyte
• integrated RAM, max.	256 kbyte
• expandable RAM	Yes; with Memory Card (RAM)
• expandable RAM, max.	64 Mbyte
Backup	
• present	Yes
• with battery	Yes; all data

- without battery

No

Battery

Backup battery

- Backup current, typ. 550 μ A
- Backup current, max. 1 530 μ A
- Backup time, max. 144 d
- Feeding of external backup voltage to CPU 5 V DC to 15 V DC

CPU processing times

- for bit operations, typ. 0.04 μ s
- for word operations, typ. 0.04 μ s
- for fixed point arithmetic, typ. 0.04 μ s
- for floating point arithmetic, typ. 0.12 μ s

CPU-blocks

DB

- Number, max. 4 095; DB 0 reserved
- Size, max. 64 kbyte

FB

- Number, max. 2 048
- Size, max. 64 kbyte

FC

- Number, max. 2 048
- Size, max. 64 kbyte

OB

- Number, max. see instruction list
- Size, max. 64 kbyte
- Number of time alarm OBs 8
- Number of delay alarm OBs 4
- Number of cyclic interrupt OBs 9
- Number of process alarm OBs 8
- Number of multicomputing OBs 1

Nesting depth

- per priority class 24
- additional within an error OB 2

Counters, timers and their retentivity

S7 counter

- Number 2 048

Retentivity

- adjustable Yes
- lower limit 0
- upper limit 2 047

— preset	Z 0 to Z 7
Counting range	
— lower limit	0
— upper limit	999
IEC counter	
• present	Yes
• Type	SFB
S7 times	
• Number	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	No times retentive
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
Data areas and their retentivity	
retentive data area in total	Total working and load memory (with backup battery)
Flag	
• Number, max.	16 kbyte
• Retentivity available	Yes; MB 0 to MB 16383
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Local data	
• adjustable, max.	32 kbyte
• preset	16 kbyte
Address area	
I/O address area	
• Inputs	16 kbyte
• Outputs	16 kbyte
of which distributed	
— MPI/DP interface, inputs	2 kbyte
— MPI/DP interface, outputs	2 kbyte
— DP interface, inputs	8 kbyte; for each line that is operated in isochronous mode, i.e. to which an OB61 to 62 has been assigned, the distributed IO address areas are halved

— DP interface, outputs	8 kbyte; for each line that is operated in isochronous mode, i.e. to which an OB61 to 62 has been assigned, the distributed IO address areas are halved
Process image	
• Inputs, adjustable	16 kbyte
• Outputs, adjustable	16 kbyte
• Inputs, default	512 byte
• Outputs, default	512 byte
• consistent data, max.	244 byte
• Access to consistent data in process image	Yes
Subprocess images	
• Number of subprocess images, max.	15
Digital channels	
• Inputs	131 072
— of which central	131 072
• Outputs	131 072
— of which central	131 072
Analog channels	
• Inputs	8 192
— of which central	8 192
• Outputs	8 192
— of which central	8 192
Hardware configuration	
Number of expansion units, max.	21; of which 6 ER with K-bus
connectable OPs	63 without message processing, 12 with message processing
Multicomputing	Yes; 4 CPUs max. (with UR1 or UR2)
Interface modules	
• Number of connectable IMs (total), max.	6
• Number of connectable IM 460s, max.	6
• Number of connectable IM 463s, max.	4; IM 463-2
Number of DP masters	
• integrated	2
• via CP	10; CP 443-5 Extended
• via IM 467	4
• Mixed mode IM + CP permitted	No; IM 467 cannot be used with CP 443-5 Ext., IM 467 cannot be used with CP 443-1 EX40 in PROFINET IO mode
• via interface module	1; IF 964-DP
• Number of pluggable S5 modules (via adapter capsule in central device), max.	6
Number of operable FMs and CPs (recommended)	
• FM	Limited by number of slots and number of connections

• CP, PtP	CP 440: Limited by number of slots; CP 441: limited by number of connections
• CP, LAN	Limited by number of slots and number of connections
• PROFIBUS and Ethernet CPs	14; incl. CP 443-5 Ext. and IM 467
Slots	
• required slots	2
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Resolution	1 ms
• Deviation per day (buffered), max.	1.7 s; Power on
• Deviation per day (unbuffered), max.	8.6 s; Power off
Operating hours counter	
• Number	8
• Number/Number range	0 to 7
• Range of values	0 to 32767 hours
• Granularity	1 h
• retentive	Yes
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• to DP, master	Yes
• to DP, slave	Yes
• in AS, master	Yes
• in AS, slave	Yes
• to IF 964 DP	Yes; as Master or Slave
1. Interface	
Interface type	Integrated
Physics	RS 485 / PROFIBUS
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	150 mA
Number of connection resources	MPI: 44, DP: 32
Protocols	
• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
MPI	
• Number of connections	44
• Transmission rate, max.	12 Mbit/s

Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
PROFIBUS DP master	
• Number of connections, max.	32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
PROFIBUS DP slave	
• GSD file	http://www.ad.siemens.de/csi_e/gsd
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— PG/OP communication	Yes
— Routing	Yes
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte

2. Interface	
Interface type	Integrated
Physics	RS 485 / PROFIBUS
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	150 mA
Number of connection resources	32
Protocols	
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
PROFIBUS DP master	
• Number of connections, max.	32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	125
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
PROFIBUS DP slave	
• GSD file	http://www.ad.siemens.de/csi_e/gsd
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— Routing	Yes
Transfer memory	

— Inputs	244 byte
— Outputs	244 byte

3. Interface

Interface type	Pluggable interface module (IF), technical data as for 2nd interface
Plug-in interface modules	IF 964-DP

Isochronous mode

Isochronous operation (application synchronized up to terminal)	Yes
Equidistance	Yes
User data per isochronous slave, max.	244 byte
shortest clock pulse	1 ms
max. cycle	32 ms

Communication functions

PG/OP communication	Yes
• Number of connectable OPs without message processing	63
• Number of connectable OPs with message processing	12

Global data communication	
• supported	Yes
• Number of GD loops, max.	16
• Number of GD packets, transmitter, max.	16
• Number of GD packets, receiver, max.	32
• Size of GD packets, max.	64 byte
• Size of GD packet (of which consistent), max.	1 variable

S7 basic communication	
• supported	Yes; in MPI mode via: SFC X_SEND, X_RCV, X_GET and X_PUT; in DP master mode via: SFC I_GET and I_PUT
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	1 variable

S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	64 kbyte
• User data per job (of which consistent), max.	462 byte; 1 variable

S5 compatible communication	
• supported	Yes; Via FC AG_SEND and AG_RECV, max. via 10 CP 443-1 or 443-5
• User data per job, max.	8 kbyte
• User data per job (of which consistent), max.	240 byte

Standard communication (FMS)	
• supported	Yes; Via CP and loadable FB
Number of connections	
• overall	64
• usable for PG communication	
— reserved for PG communication	1
• usable for OP communication	
— reserved for OP communication	1
S7 message functions	
Number of login stations for message functions, max.	12
Symbol-related messages	Yes
Program alarms	Yes
simultaneously active Alarm-S blocks, max.	200; ALARM_S/SQ blocks or ALARM_D/DQ blocks
Alarm 8-blocks	Yes
• Number of instances for alarm 8 and S7 communication blocks, max.	1 800
• preset, max.	600
Process control messages	Yes
Number of archives that can log on simultaneously (SFB 37 AR_SEND)	32
Number of messages	
• overall, max.	1 024
• in 100 ms grid, max.	128
• in 500 ms grid, max.	512
• in 1000 ms grid, max.	1 024
Number of additional values	
• with 100 ms grid, max.	1
• with 500, 1000 ms grid, max.	10
Test commissioning functions	
Status block	Yes
Single step	Yes
Number of breakpoints	4
Status/control	
• Status/control variable	Yes
• Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
• Number of variables, max.	70
Forcing	
• Forcing	Yes
• Forcing, variables	Inputs/outputs, bit memories, distributed I/Os
• Number of variables, max.	512
Diagnostic buffer	

- present Yes
- Number of entries, max. 3 200
 - adjustable Yes
 - preset 120

Configuration

Configuration software

- STEP 7 Yes

Programming

- Command set see instruction list
- Nesting levels 8
- Access to consistent data in process image Yes
- System functions (SFC) see instruction list
- System function blocks (SFB) see instruction list

Programming language

- LAD Yes
- FBD Yes
- STL Yes
- SCL Yes
- CFC Yes
- GRAPH Yes
- HiGraph® Yes

Number of simultaneously active SFCs

- DPSYC_FR 2
- D_ACT_DP 4
- RD_REC 8
- WR_REC 8
- WR_PARM 8
- PARM_MOD 1
- WR_DPARM 2
- DPNRM_DG 8
- RDSYSST 8; 1 to 8
- DP_TOPOL 1

Number of simultaneously active SFBs

- RDREC 8
- WRREC 8

Know-how protection

- User program protection/password protection Yes

Dimensions

- Width 50 mm
- Height 290 mm
- Depth 219 mm

Weights

Weight, approx.

1 070 g

last modified:

06/21/2018 