

SIMATIC DP, ET 200M INTERFACE IM 153-2 HIGH FEATURE FOR  
MAX. 8 S7-300 MODULES, WITH REDUNDANCY, TIME  
STAMPING FIT FOR ISOCHRONOUS MODE

### General information

Vendor identification (VendorID)	801Eh
----------------------------------	-------

### Supply voltage

Rated value (DC)	Yes
<ul style="list-style-type: none"> <li>• 24 V DC</li> </ul>	
external protection for power supply lines (recommendation)	not necessary

### Input current

Current consumption, max.	550 mA; at 24 V DC
Inrush current, typ.	2.5 A
$I^2t$	0.1 A <sup>2</sup> ·s

### Output voltage

Rated value (DC)	5 V
------------------	-----

### Output current

for backplane bus (5 V DC), max.	1 A
----------------------------------	-----

### Power loss

Power loss, typ.	5 W
------------------	-----

### Address area

Addressing volume	
<ul style="list-style-type: none"> <li>• Inputs</li> <li>• Outputs</li> </ul>	128 byte
	128 byte

### Time stamping

Accuracy	10 ms; 10 ms / 3 ms
Number of message buffers	15
Messages per message buffer	20
Number of stampable digital inputs, max.	128
Time format	RFC 1119 Internet (ISP)
Time resolution	1 ms
Time interval for transmitting the message buffer if a message is present	1 000 ms
Time stamp on signal change	rising / falling edge as signal entering or exiting

### Interfaces

Interface physics, RS 485	Yes
<b>PROFIBUS DP</b>	
• Node addresses	1 to 125 permitted
• automatic detection of transmission rate	Yes
• Transmission rate, max.	12 Mbit/s
• SYNC capability	Yes
• FREEZE capability	Yes
• Direct data exchange (slave-to-slave communication)	Yes; Sender
• Design of electrical connection of PROFIBUS interface	RS 485

## 1. Interface

<b>DP slave</b>	
• GSD file	(for DPV1) SIEM801E.GSD; SI01801E.GSG (for IM 153-2AA0x); SI02801E.GSG (for IM 153-2BA0x)
• automatic baud rate search	Yes

## Protocols

Bus protocol/transmission protocol	PROFIBUS DP to EN 50170
------------------------------------	-------------------------

## Isolation

Isolation tested with	Isolation voltage 500 V
-----------------------	-------------------------

## Degree and class of protection

IP degree of protection	IP20
-------------------------	------

## Ambient conditions

<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	60 °C
<b>Altitude during operation relating to sea level</b>	
• Installation altitude above sea level, max.	3 000 m

## Configuration

<b>Configuration software</b>	
• STEP 7	Yes; STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file

## Dimensions

Width	40 mm
Height	125 mm
Depth	117 mm

## Weights

Weight, approx.	360 g
<b>last modified:</b>	03/08/2018 