

PanelView Standard 550 Terminals Conversions

See the tables in this section for primary and secondary conversions for PanelView Standard 550 terminals.

PanelView Standard 550 Terminals Primary Replacement Options

PanelView Standard Terminals						PanelView Plus 7 Terminals – Primary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Adapter Plate Cat. No.	Notes
		Height mm (in.)	Width mm (in.)				Height mm (in.)	Width mm (in.)				
550	2711-K5A1	144 (5.66)	243 (9.55)	256 x 128	Remote I/O	2711P-T6C21D85	123 (4.84)	156 (6.14)	640 x 480	One Ethernet port	N/A	PanelView Plus 7 Standard 6-in. terminal benefits: Higher resolution Application limits: • Max. screen count: 25 • Max. alarm messages: 200 • Max. number of controllers: 1 Communication = Ethernet (dual Ethernet ports are available). Operator input = only touch. Power input = only DC. Conformal coat = No.
	2711-K5A1L1				DeviceNet							
	2711-K5A10											
	2711-K5A10L1											
	2711-K5A14											
	2711-K5A14L1											
	2711-K5A12				RS-232							
	2711-K5A12L1				RS-232 (DF1)							
	2711-K5A16											
	2711-K5A16L1				ControlNet							
	2711-K5A15											
	2711-K5A15L1				DH-485							
	2711-K5A2											
	2711-K5A2L1											
	2711-K5A3											
	2711-K5A3L1				RS-232 (DH-485)							
	2711-K5A5											
	2711-K5A5L1											
	2711-K5A9											
	2711-K5A9L1				DH+							
	2711-K5A8											
	2711-K5A8L1				EtherNet/IP							
	2711-K5A20											
	2711-K5A20L1				Remote I/O							
	2711-B5A1											
	2711-B5A1L1				DeviceNet							
	2711-B5A10											
	2711-B5A10L1											
	2711-B5A14											
	2711-B5A14L1				RS-232							
	2711-B5A12											
	2711-B5A12L1				RS-232 (DF1)							
	2711-B5A16											
	2711-B5A16L1											

PanelView Standard 550 Terminals Secondary Replacement Options

PanelView Standard Terminals						PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Adapter Plate Cat. No.	Notes
		Height mm (in.)	Width mm (in.)				Height mm (in.)	Width mm (in.)				
550	2711-K5A1	144 (5.66)	243 (9.55)	256 x 128	Remote I/O	2711P-B7C22A9p ⁽¹⁾	142 (5.59)	237 (9.33)	640 x 480	Dual Ethernet ports	N/A	PanelView Plus 7 Performance 6.5-in. terminal benefits: • Higher resolution • DLR Communication = Ethernet. Operator input = keypad and touch. Power input = AC or DC. ⁽¹⁾ Conformal coat = No.
					2711P-B7C22D9P							
	2711-K5A10					2711P-B7C22A9p ⁽¹⁾						
	2711-K5A10L1					2711P-B7C22D9P						
	2711-K5A14					2711P-B7C22A9p ⁽¹⁾						
	2711-K5A14L1					2711P-B7C22D9P						
	2711-K5A12					2711P-B7C22A9p ⁽¹⁾						
	2711-K5A12L1					2711P-B7C22D9P						
	2711-K5A16					2711P-B7C22A9p ⁽¹⁾						
	2711-K5A16L1					2711P-B7C22D9P						
	2711-K5A15					2711P-B7C22A9p ⁽¹⁾						
	2711-K5A15L1					2711P-B7C22D9P						
	2711-K5A2					2711P-B7C22A9p ⁽¹⁾						
	2711-K5A2L1					2711P-B7C22D9P						
	2711-K5A3					2711P-B7C22A9p ⁽¹⁾						
	2711-K5A3L1					2711P-B7C22D9P						
	2711-K5A5					2711P-B7C22A9p ⁽¹⁾						
	2711-K5A5L1					2711P-B7C22D9P						
	2711-K5A9					2711P-B7C22A9p ⁽¹⁾						
	2711-K5A9L1					2711P-B7C22D9P						
	2711-K5A8					2711P-B7C22A9p ⁽¹⁾						
	2711-K5A8L1					2711P-B7C22D9P						
	2711-K5A20					2711P-B7C22A9p ⁽¹⁾						
	2711-K5A20L1					2711P-B7C22D9P						
	2711-B5A1					2711P-B7C22A9p ⁽¹⁾						
	2711-B5A1L1					2711P-B7C22D9P						
	2711-B5A10					2711P-B7C22A9p ⁽¹⁾						
	2711-B5A10L1					2711P-B7C22D9P						
	2711-B5A14					2711P-B7C22A9p ⁽¹⁾						
	2711-B5A14L1					2711P-B7C22D9P						
	2711-B5A12					2711P-B7C22A9p ⁽¹⁾						
	2711-B5A12L1					2711P-B7C22D9P						
	2711-B5A16					2711P-B7C22A9p ⁽¹⁾						
2711-B5A16L1		2711P-B7C22D9P										