

SIMATIC S7-300, ANALOG INPUT SM 331, OPTICALLY ISOLATED, 8 AI, 13 BIT RESOLUTION, U/I/RESISTANCE/PT100, NI100, NI1000, LG-NI1000, 66 MS MODULE UPDATE, 1 X 40 PIN

Input current	
from backplane bus 5 V DC, max.	90 mA
Power loss	
Power loss, typ.	0.4 W
Analog inputs	
Number of analog inputs	8
• For resistance measurement	8
permissible input voltage for voltage input (destruction limit), max.	30 V; 12 V continuous, 30 V for max. 1 s
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	Yes
• Resistance	Yes
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
• Input resistance (0 to 10 V)	100 kΩ
• 1 V to 5 V	Yes
• Input resistance (1 V to 5 V)	100 kΩ
• 1 V to 10 V	No
• -1 V to +1 V	Yes
• Input resistance (-1 V to +1 V)	100 kΩ
• -10 V to +10 V	Yes
• Input resistance (-10 V to +10 V)	100 kΩ
• -2.5 V to +2.5 V	No
• -250 mV to +250 mV	No
• -5 V to +5 V	Yes
• Input resistance (-5 V to +5 V)	100 kΩ
• -50 mV to +50 mV	Yes
• Input resistance (-50 mV to +50 mV)	100 kΩ
• -500 mV to +500 mV	Yes

• Input resistance (-500 mV to +500 mV)	100 k Ω
• -80 mV to +80 mV	No
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
• Input resistance (0 to 20 mA)	50 Ω
• -10 mA to +10 mA	No
• -20 mA to +20 mA	Yes
• Input resistance (-20 mA to +20 mA)	50 Ω
• -3.2 mA to +3.2 mA	No
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	50 Ω
Input ranges (rated values), thermocouples	
• Type B	No
• Type C	No
• Type E	No
• Type J	No
• Type K	No
• Type L	No
• Type N	No
• Type R	No
• Type S	No
• Type T	No
• Type U	No
• Type TXK/TXK(L) to GOST	No
Input ranges (rated values), resistance thermometer	
• Cu 10	No
• Ni 100	Yes; Standard/climate
• Input resistance (Ni 100)	100 M Ω
• Ni 1000	Yes
• Input resistance (Ni 1000)	100 M Ω
• LG-Ni 1000	Yes; Standard/climate
• Input resistance (LG-Ni 1000)	100 M Ω
• Ni 120	No
• Ni 200	No
• Ni 500	No
• Pt 100	Yes; Standard/climate
• Input resistance (Pt 100)	100 M Ω
• Pt 1000	No
• Pt 200	No
• Pt 500	No
Input ranges (rated values), resistors	

• 0 to 150 ohms • 0 to 300 ohms • 0 to 600 ohms • Input resistance (0 to 600 ohms) • 0 to 6000 ohms • Input resistance (0 to 6000 ohms)	No No Yes 100 MΩ Yes 100 MΩ
Characteristic linearization	
• parameterizable — for resistance thermometer	Yes yes; Pt100 standard/air con.; Ni100 standard/air con.; Ni1000 standard/air con.; LG-Ni1000 standard/air con.
Cable length	
• shielded, max.	200 m; max. 50 m at 50 mV
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max. • Integration time, parameterizable • Basic conversion time (ms) • Interference voltage suppression for interference frequency f1 in Hz	13 bit Yes; 60 / 50 ms 66 / 55 ms 50 / 60 Hz
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer • for current measurement as 4-wire transducer • for resistance measurement with two-wire connection • for resistance measurement with three-wire connection • for resistance measurement with four-wire connection	Yes; with external supply Yes Yes Yes Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-) • Current, relative to input range, (+/-) • Resistance, relative to input range, (+/-) • Resistance thermometer, relative to input range, (+/-)	0.6 %; ±0.6 % (±5 V, 10 V, 1 to 5 V, 0 to 10 V); ±0.5 % (±50 mV, 500 mV, 1 V) 0.5 %; ±20 mA, 0 to 20 mA, 4 to 20 mA 0.5 %; 0 to 6 kohms, 0 to 600 kohms 1 Kelvin (Pt100, Ni100, climatic; Ni1000, LG-Ni1000, standard; Ni1000, LG-Ni1000, climatic); 1.2 Kelvin (Pt100, Ni100, standard)
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.4 %; 0.4% (±5 V, 10 V, 1 to 5 V, 0 to 10 V); 0.3% (±50 mV, 500 mV, 1 V)

- Current, relative to input range, (+/-) 0.3 %; ± 20 mA, 0 to 20 mA, 4 to 20 mA
- Resistance, relative to input range, (+/-) 0.3 %; 0 to 6 kohms, 0 to 600 kohms
- Resistance thermometer, relative to input range, (+/-) 1 Kelvin (Pt100, Ni100, standard); 0.8 Kelvin (Pt100, Ni100, climatic; Ni1000, LG-Ni1000, standard; Ni1000, LG-Ni1000, climatic)

Interrupts/diagnostics/status information

Diagnostics function	No
Alarms	
• Diagnostic alarm	No
• Limit value alarm	No
Diagnostic messages	
• Diagnostic information readable	No
Diagnostics indication LED	
• Group error SF (red)	No

Potential separation

Potential separation analog inputs	
• between the channels and backplane bus	Yes

Isolation

Isolation tested with	500 V DC
-----------------------	----------

Connection method

required front connector	40-pin
--------------------------	--------

Dimensions

Width	40 mm
Height	125 mm
Depth	117 mm

Weights

Weight, approx.	250 g
-----------------	-------

last modified: 07/14/2019 