


SIMATIC OPERATOR PANEL OP 73MICRO FOR SIMATIC S7-200
3" LC DISPLAY, BACKLIT WITH GRAPHICS CAPABILITY
CONFIGURABLE WINCC FLEXIBLE 2004 MICRO HSP UPWARDS;
CONTAINS OPEN-SOURCE-SW, WHICH IS PROVIDED FREE OF
CHARGE. FOR DETAILS SEE ENCLOSED CD



General information

Customer-specific configuration	No
---------------------------------	----

Display

Design of display	STN
Screen diagonal	3 in
Number of grayscales	0
Number of colors	2
Color type	Black/white

Resolution (pixels)

- | | |
|-------------------------------|-----------|
| • Horizontal image resolution | 160 Pixel |
| • Vertical image resolution | 48 Pixel |

Backlighting

- | | |
|--------------------------------|-----------|
| • MTBF backlighting (at 25 °C) | 100 000 h |
|--------------------------------|-----------|

Control elements

Control elements	Membrane keyboard
------------------	-------------------

Keyboard fonts

- | | |
|--------------------------------------|----|
| • Membrane keyboard | |
| — user-definable label membrane keys | No |

• Function keys	
— Number of function keys	4
— Number of function keys with LEDs	0
• System keys	Yes
• Numeric/alphabetical input	Yes / Yes
— hexadecimal keyboard	Yes
• Multi-key operation	Yes
Touch operation	
• Design as touch screen	No
Connection type	
• Connection for mouse/keyboard/barcode reader	- / - / -
Installation type/mounting	
Mounting position	vertical
maximum permissible angle of inclination without external ventilation	80°
Supply voltage	
Type of supply voltage	DC
Input current	
Current consumption (rated value)	0.1 A
Starting current inrush I ² t	0.5 A ² ·s
Processor	
Processor type	ARM
Memory	
Type of memory	Flash
Memory available for user data	128 kbyte
Time of day	
Clock	
• Type	Software clock, no battery backup
• retentive	No
• synchronizable	No
Interfaces	
Interfaces/bus type	1 x RS485 (max. 187.5 kbit/s)
Number of RS 485 interfaces	1
• Transmission rate, max.	187.5 kbit/s
Protocols	
Supports protocol for PROFINET IO	No
PROFIsafe	No
PROFIBUS	Yes

Protocols (Ethernet)	
• TCP/IP	No
Further protocols	
• EtherNet/IP	No
• MODBUS	No
• other bus systems	Yes
Degree and class of protection	
Front	IP65, NEMA 4x (when installed)
IP (at the front)	IP65
IP (rear)	IP20
Standards, approvals, certificates	
Certifications	CE, GL, ABS, BV, DNV, LRS, UL, CSA, cULus, C-TICK, NEMA 4x
cULus	Yes
EAC (formerly Gost-R)	No
Suitable for safety functions	No
Marine approval	
• Germanischer Lloyd (GL)	Yes
• American Bureau of Shipping (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (Class NK)	Yes
• Polski Rejestr Statkow (PRS)	No
Use in hazardous areas	
• FM Class I Division 2	No
• EX zone 2	No
• EX zone 22	No
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	90 %
Operating systems	
pre-installed operating system	LINUX
Configuration	

Message indicator	Yes
Alarm system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes
Configuration software	
• STEP 7 Basic (TIA Portal)	No
• STEP 7 Professional (TIA Portal)	No
• WinCC flexible Compact	Yes
• WinCC flexible Standard	Yes
• WinCC flexible Advanced	Yes
• WinCC Basic (TIA Portal)	No
• WinCC Comfort (TIA Portal)	No
• WinCC Advanced (TIA Portal)	No
• WinCC Professional (TIA Portal)	No
• Configuration tool	WinCC flexible Micro Version 2004 SP1, HSP or higher (to be ordered separately)
Languages	
Online languages	
• Number of online/runtime languages	5
Project languages	
• Languages per project	32
Functionality under WinCC (TIA Portal)	
Libraries	Yes
Task planner	Yes
Help system	Yes
• Number of characters per info text	320
• Number of tooltips	0
Message system	
• Number of alarm classes	32
• Number of messages	250
• Bit messages	Yes
— Number of bit messages	250
• Analog messages	Yes
— Number of analog messages	5
• Telegram message procedure Alarm S	No
• System messages HMI	Yes
• System messages PLC	Yes
• System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)	No
• Number of characters per message	80

• Number of process values per message	8
• Message indicator	Yes
• acoustic feedback	No
• First/last value	Yes
Variables	
• Number of variables per device	500
• Number of variables per screen	20
• Limit values	Yes
• Multiplexing	Yes
• Structures	Yes
Images	
• Number of configurable images	250
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	No
• Image number in the PLC	No
Image objects	
• Text objects	1,000 text elements
• Number of I/O fields per image	20
• Number of date/time fields	0
• Index of screen context	No
• Return	Yes
• Graphics object	Bit maps, icons, icon (full-screen)
— Icons	250
— Icon (full screen)	25
Complex image objects	
• Status/control	Not possible
• dynamic objects	Bar graphs
— Number of curve diagrams per image	0
• Bar graphs	
— Number of bars per chart	5
• Sliders	
— Number of slides per image	0
• Pointer instruments	
— Number of analog indicators per image	0
• Limit value lines	Yes
• Number of alphanumerical fields	0
— alphanumeric fields per image	0
• Number of numerical fields	0
— numerical fields per image	0
• Number of password fields	0

• Number of visible switches per project	0
— visible switches per image	0
— hidden switches per image	0
• Number of status switches per project	0
— Number of status switches per image	0
• Number of selector switches per project	0
— Selector switches per image	0
• Number of decade switches per project	0
— Decade switches per image	0
• Number of signal lamps per project	0
— Signal lamps per image	0
Attributes for dynamic objects	
• Color change	No
• X/Y movement	No
• Hide	Yes
• Angle of rotation	No
Lists	
• Number of text lists per project	150
• Number of graphics lists per project	0
Security	
• Number of user groups	1
• Number of users	1
• Password export/import	Yes
Transfer (upload/download)	
• Transfer of configuration	serial
Process coupling	
• Connection to controller	for S7-200, see section on "System interfaces"
• S7-200	Yes
— PPI (point-to-point)	Yes
— PPI network	Yes
— MPI	Yes
— PROFIBUS DP	No
• S7-300/400	No
— MPI	No
— PROFIBUS DP	No
— PROFINET	No
• S5	No
— serial	No
— PROFIBUS DP	No
• TI 505	No
• Allen Bradley (DF1)	No

• Allen Bradley (DF485)	No
• Mitsubishi (FX)	No
• Mitsubishi (MP4)	No
• Telemecanique (ADJUST)	No
• Telemecanique (Uni-Telway)	No
• OMRON (LINK/Multilink)	No
• Modicon (Modbus)	No
• GE-Fanuc (SNP)	No
Functions	
• Key repeat	Yes
• TAB sequence	Yes
• Calculating functions	Yes
• Animate	No
• Menu tree editor	No
• Unit switchover	No
Service tools/configuration aids	
• Clean screen	No
• Touch calibration	No
• Backup/Restore manually	Yes
• Simulation	No
• Device switchover	Yes
• Delta transfer	No
• Monitoring function for battery and memory	No
• Trace (operation archive)	No
Expandability/openness	
• Open Platform Program	No
Peripherals/Options	
Peripherals	
• SIMATIC HMI MM memory card: Multi Media Card	No
Additional software components loadable	Yes
Dimensions	
Width of the housing front	154 mm
Height of housing front	84 mm
Mounting cutout, width	138 mm
Mounting cutout, height	68 mm
Overall depth	28.5 mm
Weights	
Weight (without packaging)	0.25 kg
Other	

free hotline	Yes
Warranty period	1 y
last modified:	04/28/2017 