SIEMENS

Data sheet 6DL1135-6TF00-0EH1

Siemens EcoTech

SIMATIC ET 200SP HA, analog output module, AQ 8XI HART HA suitable for terminal block H1, M1, color code CC00, channel diagnostics, 16-bit, +/-0.1%



Figure similar

General information	
Product type designation	AQ 8 x I HART HA
Firmware version	V1.0
● FW update possible	Yes
Usable terminal block	type H1, M1, N0, H0, M0 (for details see the system manual)
Color code for module-specific color-coded label	CC00
Product function	
● I&M data	Yes; I&M0 to I&M3
Engineering with	
● SPPA-T3000 can be configured/integrated from version	V8.0
Redundancy	
● Redundancy capability	Yes; With TB type M1
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	230 mA; 8x 20 mA with 750 ohm load resistance
Current consumption, max.	350 mA; 8x 24 mA with 750 ohm load resistance
Power loss	
Power loss, typ.	3.2 W
Address area	
Address space per module	
● Address space per module with MultiHART, max.	28 byte; PII: 0 bytes, +1 byte for QI information, +6 bytes for HART, +2 bytes of PROFINET status data; PIO: 16 bytes, +1 byte for HART, +2 bytes of PROFINET status data
Analog outputs	
Number of analog outputs	8; short-circuit proof with respect to ground
Current output, no-load voltage, max.	28 V
Output ranges, current	
● 0 to 10 mA	Yes; 14 bit
● 0 to 20 mA	Yes; 15 bit
● -20 mA to +20 mA	No
● 4 mA to 20 mA	Yes; 16 bit incl. sign

Subject to change without notice
© Copyright Siemens

Connection of actuators	
● for current output two-wire connection	Yes
Load impedance (in rated range of output)	
● for current outputs, min.	150 Ω
● with current outputs, max.	750 Ω
● with current outputs, inductive load, max.	10 mH
Destruction limits against externally applied voltages and currents	
● Voltages at the outputs	36 V; Minus 0.3 V lower limit
Cable length	
● shielded, max.	1 000 m
Analog value generation for the outputs	
Settling time	
● for resistive load	1.2 ms; 750 ohm
● for inductive load	1.2 ms
Errors/accuracies	
Linearity error (relative to output range), (+/-)	0.01 %
Temperature error (relative to output range), (+/-)	0.002 %/K
Crosstalk between the outputs, min.	70 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.02 %
Operational error limit in overall temperature range	
● Current, relative to output range, (+/-)	0.5 %; 0 ... 60 °C: 0.2 %
Basic error limit (operational limit at 25 °C)	
● Current, relative to output range, (+/-)	0.1 %
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnoses	
● Monitoring the supply voltage	Yes
● Wire break	Yes; channel by channel
● Short-circuit	Yes; channel by channel
● Overflow/Underflow	Yes; channel by channel
Diagnostics indication LED	
● MAINT LED	Yes; Yellow LED
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	Yes; red LED
● for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
● Between the channels and load voltage L+	Yes
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C
● horizontal installation, max.	70 °C
● vertical installation, min.	-40 °C
● vertical installation, max.	60 °C
Dimensions	
Width	22.5 mm
Height	115 mm
Depth	138 mm
Weights	
Weight, approx.	160 g

Subject to change without notice
© Copyright Siemens

Classifications

	Version	Classification
eClass	16	27-24-26-01
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596

Approvals / Certificates

General Product Approval

CE EG-Konf. | Miscellaneous | UKCA | Declaration of Conformity | RCM | EAC

General Product Approval | For use in hazardous locations

China RoHS | Miscellaneous | CE EG-Konf. | UKCA | Manufacturer Declaration | IECEx

For use in hazardous locations

Declaration of Conformity | CCC | UL | ATEX | IECEx | Miscellaneous

Maritime application

ABS | Bureau Veritas | DNV | NK / Nippon Kaiji Kyokai | RINA | CCS (China Classification Society)

Environment

Siemens EcoTech | EPD

last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens