SIEMENS

Data sheet 6GK7443-1EX11-0XE0

Product type designation

CP 443-1

COMMUNICATIONSPROCESSOR CP443-1 FOR CONNECTION OF SIMATIC S7-400 W. IND. ETHERN.,ISO/TCP/IP AND UDP S7 COMM.,FETCH/WRITE, DIAGNOST. EXPANSIONS, SEND/RECEIVE, WITH AND W/O RFC 1006, MULTICAST, NTP, INITIALIZING THROUGH LAN ACCESS PROTECTION USING IP-ACCESS LIST, 10/100 MBIT



Transmission rate	
Transfer rate	
• at the 1st interface	10 ... 100 Mbit/s

Interfaces	
Number of interfaces / acc. to Industrial Ethernet	1
Number of electrical connections	
• at the 1st interface / acc. to Industrial Ethernet	1
Type of electrical connection	
• at the 1st interface / acc. to Industrial Ethernet	RJ45 port / AUI
• of Industrial Ethernet interface	15 pin Sub-D-socket (10Mbit/s AUI, 10/100 Mbit/s ITP)
design of the removable storage / C-PLUG	No

Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / 1 / from backplane bus	5 V
Supply voltage	5 V
Relative symmetrical tolerance / at DC	
• at 5 V	5 %

Subject to change without notice
© Copyright Siemens

Consumed current	
• from backplane bus / at DC / at 5 V / typical	1.4 A
Power loss [W]	8.6 W

Permitted ambient conditions	
Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight	
Module format	Compact module S7-400 single width
Width	25 mm
Height	290 mm
Depth	210 mm
Net weight	0.7 kg

Product properties, functions, components / general	
Number of units	
• per CPU / maximum	14

Performance data / open communication	
Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	64
Amount of data	
• as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
• as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
• as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
• as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum	2 Kibyte

Performance data / S7 communication	
Number of possible connections / for S7 communication	
• maximum	48

Performance data / multi-protocol mode

Subject to change without notice
© Copyright Siemens

Number of active connections / with multi-protocol mode	64
Product function / MIB support	No
Protocol / is supported	
• SNMP v1	No
• LLDP	No
Configuration software	
• required	STEP 7 V5.1 SP2 or higher

Product functions / Diagnosis	
Product function / Web-based diagnostics	No

Product functions / switch	
Product feature / Switch	No

Product functions / Redundancy	
Product function	
• Ring redundancy	No

Product functions / Security	
Product function	
• password protection for Web applications	No
• ACL - IP-based	No
• ACL - IP-based for PLC/routing	No
• switch-off of non-required services	No
• Blocking of communication via physical ports	No
• log file for unauthorized access	No

Product functions / Time	
Product function / SICLOCK support	Yes
Product function / pass on time synchronization	No
Protocol / is supported	
• NTP	Yes

Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Subject to change without notice
© Copyright Siemens

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	06/15/2017

Subject to change without notice
© Copyright Siemens