6ES7155-6AU00-0DN0

SIMATIC ET 200SP IM 155-6 PN HS Interface Module

Siemens 6ES7155-6AU00-0DN0 is the IM 155-6 PN HS interface module for ET 200SP, supporting up to 30 I/O modules, 125 µs isochronous operation, and multi-hot swapping.

PRODUCT ENQUIRY

Email: **info@apterpower.com**
Phone / WhatsApp: **+86 18106909650**
Website: **www.apter.com**

Product overview

Siemens 6ES7155-6AU00-0DN0 is the IM 155-6 PN HS interface module for a SIMATIC ET 200SP station. It supports up to 30 ET 200SP I/O modules, 125 submodules, and up to 968 bytes of station address space.

The PROFINET interface is implemented through a supported BusAdapter and presents two switched ports. The module supports IRT from 125 µs to 4 ms, isochronous operation, MRP and MRPD media redundancy, prioritized startup, Shared Device operation, and open TCP/IP services.

Multi-hot swapping allows module exchange during operation within the engineered station design. Before replacement, confirm firmware, BusAdapter type, TIA Portal or STEP 7 integration, station name, network parameters, and the role of the server module included with the interface module.

Technical specifications

Parameter	Value
Model Number	6ES7155-6AU00-0DN0
Product Family	SIMATIC ET 200SP
Product Type	IM 155-6 PN HS
Hardware Functional Status	From FS02
Firmware Version	V4.0
Firmware Update	Supported
I&M; Data	I&M0; to I&M3;
Hot Swapping	Multi-hot swapping
Isochronous Mode	Yes
TIA Portal Integration	V14 or higher
STEP 7 Integration	V5.5 SP4 or higher
GSDML Revision	V2.32
Rated Supply	24 V DC
Permissible Supply Range	19.2 to 28.8 V DC
Maximum Current Consumption	500 mA
Typical Power Loss	1.7 W
Maximum ET 200SP Modules	30
Maximum Submodules	125
PROFINET Interfaces	1; two switched ports
Maximum Shared Device Controllers	4
PROFINET Transfer	100 Mbit/s full duplex
Minimum IRT Cycle	125 µs
Maximum Isochronous Cycle	4 ms
Maximum Jitter	0.25 µs
Horizontal Operating Temperature	-25 to 60 °C
Vertical Operating Temperature	-25 to 50 °C
Maximum Installation Altitude	5000 m
Width	50 mm
Height	117 mm
Depth	74 mm
Approximate Weight	147 g without BusAdapter

Source: Siemens data sheet for 6ES7155-6AU00-0DN0

SIEMENS

Data sheet 6ES7155-6AU00-0DN0

SIMATIC ET 200SP, PROFINET interface module IM155-6PN High Speed max. 30 I/O modules, 0.125 ms isochronous mode Multi-hotswap, incl. server module

General information	
Product type designation	IM 155-6 PN HS
HW functional status	From FS02
Firmware version	V4.0
● FW update possible	Yes
Product function	
● I&M data	Yes; I&M0 to I&M3
● Module swapping during operation (hot swapping)	Yes; Multi-hot swapping
● Isochronous mode	Yes
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V14
● STEP 7 configurable/integrated from version	V5.5 SP4
● PROFINET from GSD version/GSD revision	GSDML V2.32
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
● Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption, max.	500 mA
Inrush current, max.	4.5 A
I^2t	0.09 $A^2 \cdot s$
Power loss	
Power loss, typ.	1.7 W
Address area	
Address space per module	
● Address space per module, max.	32 byte; For input and output data respectively
Address space per station	
● Address space per station, max.	968 byte
Hardware configuration	
Rack	
● Quantity of operable ET 200SP modules, max.	30
● Quantity of operable ET 200AL modules, max.	0
Submodules	
● Number of submodules per station, max.	125
Interfaces	
Number of PROFINET interfaces	1; 2 ports (switch)
1. Interface	
Interface types	
● RJ 45 (Ethernet)	Yes; with BusAdapter
● Number of ports	2; with BusAdapter
● integrated switch	Yes
● BusAdapter (PROFINET)	Yes; BA 2x RJ45, BA 2x FC, BA 2x SCRJ, BA SCRJ/RJ45, BA SCRJ/FC, BA 2x LC, BA LC/RJ45, BA LC/FC
Protocols	
● PROFINET IO Device	Yes

Subject to change without notice
© Copyright Siemens

● Open IE communication	Yes
● Media redundancy	Yes; PROFINET MRP client / HRP client
PROFINET IO Device	
Services	
— IRT	Yes; 125 µs to 4 ms in 125 µs frame
— PROFIenergy	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	4
Interface types	
RJ 45 (Ethernet)	
● Transmission procedure	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
● 100 Mbps	Yes
● Autonegotiation	Yes
● Autocrossing	Yes
Protocols	
Modbus TCP	No
Redundancy mode	
● PROFINET system redundancy (S2)	No
● H-Sync forwarding	Yes
Media redundancy	
— MRP	Yes
— MRPD	Yes
Open IE communication	
● TCP/IP	Yes
● SNMP	Yes
● LLDP	Yes
Isochronous mode	
Equidistance	Yes
shortest clock pulse	125 µs
max. cycle	4 ms
Bus cycle time (TDP), min.	125 µs
Jitter, max.	0.25 µs
Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	
● RUN LED	Yes; green LED
● ERROR LED	Yes; red LED
● MAINT LED	Yes; Yellow LED
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Connection display LINK TX/RX	Yes; 2x green link LEDs on BusAdapter
Potential separation	
between backplane bus and electronics	No
between PROFINET and all other circuits	Yes; 1500 V AC (type test)
between supply and all other circuits	No
Permissible potential difference	
between different circuits	Safety extra low voltage SELV
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Network loading class	3
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-25 °C; No condensation
● horizontal installation, max.	60 °C
● vertical installation, min.	-25 °C; No condensation
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	

Subject to change without notice
© Copyright Siemens

● Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
connection method	
ET-Connection	
● via BU/BA Send	No
Dimensions	
Width	50 mm
Height	117 mm
Depth	74 mm
Weights	
Weight, approx.	147 g; without BusAdapter

last modified: 7/13/2024

Subject to change without notice
© Copyright Siemens