

8mm Eddy Current Sensor



Non-contact sensor designed for critical turbomachinery applications such as steam, gas and hydro turbines, compressors, gearboxes, pumps and fans to measure radial and axial shaft dynamic displacement; position, eccentricity and speed.



Performance	
Linear Measurement Range	2 mm (80 mils)
Initial Air Gap	0.5 mm (20 mils)
Incremental Scale Factor (ISF)	ISO: 8 V/mm (203.2 mV/mil) ± 5% @ temperature range 0 to 45°C (+32 to +113°F)
Deviation from best fit straight line (DSL)	± 0.025 mm (± 1 mil) @ temperature range 0 to 45°C (+32 to +113°F)
Measuring Target	
Minimum Shaft Diameter	25 mm (0.79”)
Target Material (Ferromagnetic Steel)	42CrMo4 (AISI/SAE 4140) Standard Other (On Request)
Environmental, General	
Protection Class	IP66, IEC 60529
Operating Temperature Range	Sensor incl. 1m Cable: -35 to +180°C (-31 to 356°F) Cable & Connector: -35 to +150°C (-31 to 302°F)
Material	Sensor Tip (PEEK Polyether Ether Ketone), Case (Stainless Steel) Cable (PTFE Polytetrafluoroethylene), Connector (Brass, nickel-plated)
Weight (Sensor with 1m Cable)	Approx. 100 grams (3.53 oz)


Compliance and Certifications	
CE	2014/30/EU (EN 61326-1) 2014/34/EU 2011/65/EU
ATEX	EN 60079-0 EN 60079-11
IEC-Ex	IEC 60079-0 IEC 60079-11 IEC 60079-26
CSA	CAN/CSA-C22.2 NO. 0-M91 CAN/CSA-C22.2 NO. 157-92 CAN/CSA-C22.2 NO. 213-M1987 CAN/CSA-E60079-15-02 (R2006) CAN/CSA-C22.2 NO. 25-1966 CAN/CSA-C22.2 NO. 61010-1-04 ANSI/UL Standard 913-2004 ANSI/UL Standard 1604-1995 UL 60079-15 2002 UL 61010-1

Hazardous Area Approvals

Intrinsic Safety (ia)	
ATEX / IEC-Ex / CSA	Area classification depends on converter, see converter documentation for details. Sensor temperature classification: T6: Ta ≤ 64°C T4: Ta ≤ 114°C T3: Ta ≤ 160°C
Non-sparking (nA)	
ATEX / IEC-Ex / CSA	Area classification depends on converter, see converter documentation for details. Sensor temperature classification: T6: Ta ≤ 64°C T4: Ta ≤ 114°C T3: Ta ≤ 160°C

Dimensions

PR6423/xxx-xxx (Standard)



A. Case thread, M10x1 or 3/8-24UNF
B. SW 11 mm for M10 threads, SW 7/9-16 in for 3/8-24UNF threads
C. Standard cable diameter 2.8 mm (0.110 in), minimum bending radius 25 mm (0.984 in)
D. Armored cable diameter 6 mm (0.236 in), minimum bending radius 35 mm (1.378 in)
E. Optional Adapter Plug after 1m cable from Sensor
F. Cable Length (Tolerances 0... +10%)
G. Lemo connector (male), 11.0 mm (0.433 in) diameter or open cable end

Ordering Information

Tip Diameter	Case Threads	Armored Cable	Model No.
8mm	M10x1	No	PR6423/00
		Yes	PR6423/01
			PR6423/03*
	3/8"-24 UNF	No	PR6423/10
		Yes	PR6423/11
			PR6423/13*

**Armored cable option for Reverse Mount, if Adapter Plug is chosen.*


Model No.	Case Thread X	Adapter Plug X	Cable Length X	Cable End X
PR6423/00 PR6423/01 PR6423/10 PR6423/11	**0** 25mm **1** 35mm **2** 45mm **3** 55mm **4** 65mm **5** 75mm **6** 85mm **7** 95mm **8** 105mm **9** 115mm **E** 155mm **H** 195mm **R** Reverse Mount	**0** With **1** Without	**0** 4.0m **1** 5.0m **3** 8.0m **F** 9.0m **4** 10.0m	**0** Lemo* **1** Open

**Not available, if Reverse Mount without Adapter Plug is chosen.*

Example: PR6423/000-000


ECS 8mm, M10X1, NO ARMOR, 25MM SLEEVE, 1+3M CABLE, LEMO

Eddy Current Signal Converter



Sensor Signal Converter designed for critical turbo machinery applications such as steam, gas and hydro turbines, compressors, pumps and fans to measure radial and axial shaft displacement, position, eccentricity and speed/key.

Dynamic Performance		
Frequency Range (-3 dB)		0 to 20000 Hz:
Rise Time		<15 µs
Input Sensor Types		PR6422, PR6423,PR 6424, PR6425, PR6426
Extended Measuring Range		For Extended Range Use CON011/91x-xxx
NOTE: PR6425 requires extended range converter		
Environmental		
Operating Temperature Range		-30 to 100°C (-22 to 212°F)
Shock and Vibration		5g @ 60 Hz @ 25°C (77°F)
Protection Class		IP65
Power & Electrical		
Supply Voltage Range		-23V to -32V (Output Range - 4V to -20V)
		-21V to -32V (Output Range - 2V to -18V)
Physical		
Housing Material		GD-ALSi9Cu3
Weight		~600 grams (21.16 oz)
Mounting		4 Screws M5x20 (Included in Delivery)
Connections:	Transducer	Self-Locking Lemo-Plug
	Supply/Output	Spring Type (Max. 1.5Mm²)
Compliance and Certifications		
CE		2014/30/EU (EN 61326-1)
		2014/34/EU
		2011/65/EU
ATEX		EN 60079-0
		EN 60079-11



IEC-Ex	IEC 60079-0
	IEC 60079-11
	IEC 60079-26
CSA	CAN/CSA-C22.2 NO. 0-M91
	CAN/CSA-C22.2 NO. 157-92
	CAN/CSA-C22.2 NO. 213-M1987
	CAN/CSA-E60079-15-02 (R2006)
	CAN/CSA-C22.2 NO. 25-1966
	CAN/CSA-C22.2 NO. 61010-1-04
	ANSI/UL Standard 913-2004
	ANSI/UL Standard 1604-1995
	UL 60079-15 2002
	UL 61010-1

Hazardous Area Approvals

Intrinsic Safety (iA)	
ATEX	II 1 G Ex ia IIC T6 Ga, -20°C ≤ Ta ≤ 60°C (Use with current limiting, e.g.: safety barrier)
IEC-Ex	Ex ia IIC T6 Ga, -20°C ≤ Ta ≤ 60°C (Use with current limiting, e.g.: safety barrier)
CSA	Class I Division 1, Groups A, B, C, D, T6
	Class II, III Division 1, Groups E, F, G, T6
	T6: -25°C ≤ Ta ≤ 60°C (Use with current limiting, e.g.: safety barrier)
Non-sparking (nA)	
CSA	Class I Division 2, Groups A, B, C, D
	Class II, III Division 2, Groups E, F,G
	Ex nA II T6
	AEx nA II T6
	T6: -25°C ≤ Ta ≤ 60°C