

Product type designation

RF180C communication module

RFID COMMUNICATION MODULE RF180C FOR PROFINET; 2 READERS CONNECTABLE; WITHOUT CONNECTING BLOCK FOR PROFINET



Suitability for operation

PROFINET network together with RF200/300/600, MV400, MOBY D/E/U

Transmission rate

Transfer rate / for Industrial Ethernet	10 ... 100 Mbit/s
Transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s

Interfaces

Design of the interface / for point-to-point connection	RS422
Number of readers / connectable	2
Type of electrical connection	
<ul style="list-style-type: none"> • of Industrial Ethernet interface • for supply voltage 	<p>(according to the connection block)</p> <p>(according to the connection block)</p>
Design of the interface / to the reader / for communication	M12, 8-pin

Mechanical data

Material	Thermoplastic (Valox 467, fiberglass reinforced)
Color	IP Basic 714

Tightening torque / of the screw for securing the equipment / maximum	3 N·m
---	-------

Supply voltage, current consumption, power loss

Supply voltage	
<ul style="list-style-type: none"> • at DC / Rated value • at DC 	24 V 20 ... 30 V
Consumed current / at DC / at 24 V	
<ul style="list-style-type: none"> • without connected devices / typical • with connected devices / maximum 	0.1 A 1.1 A

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport 	0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
Protection class IP	IP67
Shock resistance	According to IEC 61131-2
Shock acceleration	300 m/s ²
Vibrational acceleration	100 m/s ²

Design, dimensions and weight

Width	60 mm
Height	30 mm
Depth	210 mm
Net weight	0.21 kg
Mounting type	2 x M5 screws
Wire length / for RS 422 interface / maximum	1000 m

Product properties, functions, components / general

Display version	4 LEDs per reader connection, 4 LEDs for device status
Protocol / is supported / Media Redundancy Protocol (MRP)	No
Product function / transponder file handler can be addressed	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • LLDP • PROFINET IO protocol • TCP/IP • SNMP v1 • SNMP v2 • SNMP v3 • DCP • EtherNet/IP protocol 	Yes Yes No Yes No No Yes No
Type of parameterization	GSDML

Type of computer-mediated communication	acyclic communication
---	-----------------------

Standards, specifications, approvals

Certificate of suitability	CE, FCC, cULus, PNO: Conformance Class B
MTBF	121 y

Accessories

accessories	Connection block M12 d-coded, 7/8" 5-pin or push-pull
-------------	---

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support 	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

Security information

Security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p>
----------------------	---

last modified:

06/05/2017 