SIEMENS

Data sheet 6GK7443-5DX04-0XE0

Product type designation

CP 443-5 Extended

Communications processor CP 443-5 Extended for connection of SIMATIC S7-400 to PROFIBUS DP, S5-compatible, PG/OP and S7 communication



Transmission rate	
Transfer rate	
• at the 1st interface / acc. to PROFIBUS	9.6 kbit/s ... 12 Mbit/s
Interfaces	
Number of interfaces / acc. to Industrial Ethernet	0
Number of electrical connections	
• at the 1st interface / acc. to PROFIBUS	1
Type of electrical connection	
• at the 1st interface / acc. to PROFIBUS	9-pin Sub-D socket (RS485)
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / 1 / from backplane bus	5 V
Supply voltage	5 V
Relative symmetrical tolerance / at DC	
• at 5 V	5 %
Consumed current	
• from backplane bus / at DC / at 5 V / typical	1 A

Subject to change without notice
© Copyright Siemens

Power loss [W]	5 W

Ambient conditions	
Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight	
Module format	Compact module S7-400 single width
Width	25 mm
Height	290 mm
Depth	210 mm
Net weight	0.65 kg

Product properties, functions, components / general	
Number of units	
• per CPU / maximum	14
• Note	The number of CPs that can be operated as DP masters depends on the number of CP 443-1 Advanced processors operating in the S7-400 station as PROFINET IO controllers. Up to 10 CPs can be operated in total: up to 4 as PROFINET IO controllers (CP 443-1 Advanced); up to 10 as DP masters (CP 443-5 Extended)

Performance data / open communication	
Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	32
Amount of data	
• as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum	240 byte

Performance data / PROFIBUS DP	
Service / as DP master	
• DPV1	Yes
Number of DP slaves / on DP master / usable	125
Amount of data	
• of the address area of the inputs / as DP master / total	4096 byte
• of the address area of the outputs / as DP master / total	4096 byte
• of the address area of the inputs / per DP slave	244 byte

© Copyright Siemens

• of the address area of the outputs / per DP slave	244 byte

Performance data / S7 communication

Number of possible connections / for S7 communication	
• maximum	48

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	
• without DP / maximum	59
• with DP / maximum	54

Product functions / management, configuration

Configuration software	
• required	STEP 7 V5.4 SP4 or higher and NCM S7 for PROFIBUS

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified: 08/12/2019

Subject to change without notice
© Copyright Siemens