SIEMENS

Data sheet 6ES7441-2AA03-0AE0

SIMATIC S7-400, CP 441-2 COMMUNICATIONS MODULE FOR POINT TO POINT CONNECTIONS 2 CHANNELS INCL. CONFIG. PACKAGE ON CD

Input current	
from backplane bus 5 V DC, max.	700 mA; Without interface module
Interface modules	
• 20 mA (TTY), power consumption from 5 V/24 V, max.	300 mA at 5 V, 45 mA at 24 V
• RS 422/485 (X.27), power consumption from 5 V, max.	300 mA
• RS 232C (V.24), power consumption from 5 V, max.	300 mA
Memory	
Memory requirements per interface in memory card of S7-CPU	1 to 5 KB for parameters; 0 to 55 KB for message texts; 0 to 64 KB for loadable drivers
Interfaces	
Number of interfaces	2; variable
Interface physics, 20 mA (TTY)	Yes
Interface physics, RS 232C (V.24)	Yes
Interface (physical) RS 422/485 (X.27)	Yes
20 mA (TTY), cable length shielded, max.	1 000 m
RS 232, cable length shielded, max.	10 m
RS 422/RS 485, cable length shielded, max.	1 200 m
Point-to-point	
• Transmission rate, max.	115.2 kbit/s; distributed on both interfaces
• supported printers	HP-Deskjet, HP-Laserjet, IBM-Proprinter, user-defined
Integrated protocol driver	
— 3964 (R)	Yes
— ASCII	Yes
— RK512	Yes
— Printer	Yes
— customer-specific drivers reloadable	Yes
Transmission rate, 20 mA (TTY)	
— with 3964 (R) protocol, max.	19.2 kbit/s
— with ASCII protocol, max.	19.2 kbit/s
— with printer driver, max.	19.2 kbit/s
— with RK 512 protocol, max.	19.2 kbit/s

Subject to change without notice
© Copyright Siemens

Transmission rate, RS 422/485	
— with 3964 (R) protocol, max.	115.2 kbit/s
— with ASCII protocol, max.	115.2 kbit/s
— with printer driver, max.	115.2 kbit/s
— with RK 512 protocol, max.	115.2 kbit/s
Transmission speed, RS 232	
— with 3964 (R) protocol, max.	115.2 kbit/s
— with ASCII protocol, max.	115.2 kbit/s
— with printer driver, max.	115.2 kbit/s
— with RK 512 protocol, max.	115.2 kbit/s

Communication functions

S7 communication	
• S7 extended communication	Yes
Number of connections	
• overall	8

Configuration

Configuration software	
• STEP 7	Yes; own parameter assignment forms

Dimensions

Width	25 mm
Height	290 mm
Depth	210 mm

Weights

Weight, approx.	720 g; Interface module: 100 g

last modified: 03/15/2018

Subject to change without notice
© Copyright Siemens