

PanelView Standard 600 Terminals Conversions

See the tables in this section for primary and secondary conversions for PanelView Standard 600 terminals.

PanelView Standard 600 Terminals Primary Replacement Options

PanelView Standard Terminals						PanelView Plus 7 Terminals – Primary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Adapter Plate Cat. No.	Notes
		Height mm (in.)	Width mm (in.)				Height mm (in.)	Width mm (in.)				
600	2711-K6C1	192 (7.55)	290 (11.40)	320 x 234	Remote I/O	2711P-B7C22A9P	142 (5.59)	237 (9.33)	640 x 480	Dual Ethernet ports	2711P-RAAK7	PanelView Plus 7 Performance 6.5-in. terminals benefits: • Higher resolution • DLR Communication = Ethernet. Operator input = keypad and touch. Power input = AC or DC. Conformal coat = No. Adapter plate is necessary for drop-in replacement.
	2711-K6C1L1					2711P-B7C22D9P						
	2711-K6C10				DeviceNet	2711P-B7C22A9P						
	2711-K6C10L1					2711P-B7C22D9P						
	2711-K6C14					2711P-B7C22A9P						
	2711-K6C14L1					2711P-B7C22D9P						
	2711-K6C12				RS-232	2711P-B7C22A9P						
	2711-K6C12L1					2711P-B7C22D9P						
	2711-K6C16				RS-232 (DF1)	2711P-B7C22A9P						
	2711-K6C16L1					2711P-B7C22D9P						
	2711-K6C15				ControlNet	2711P-B7C22A9P						
	2711-K6C15L1					2711P-B7C22D9P						
	2711-K6C2				DH-485	2711P-B7C22A9P						
	2711-K6C2L1					2711P-B7C22D9P						
	2711-K6C3					2711P-B7C22A9P						
	2711-K6C3L1					2711P-B7C22D9P						
	2711-K6C5				RS-232 (DH-485)	2711P-B7C22A9P						
	2711-K6C5L1					2711P-B7C22D9P						
	2711-K6C9					2711P-B7C22A9P						
	2711-K6C9L1					2711P-B7C22D9P						
	2711-K6C8				DH+	2711P-B7C22A9P						
	2711-K6C8L1					2711P-B7C22D9P						
	2711-K6C20				EtherNet/IP	2711P-B7C22A9P						
	2711-K6C20L1					2711P-B7C22D9P						
	2711-B6C1				Remote I/O	2711P-B7C22A9P						
	2711-B6C1L1					2711P-B7C22D9P						
	2711-B6C10				DeviceNet	2711P-B7C22A9P						
	2711-B6C10L1					2711P-B7C22D9P						
	2711-B6C14					2711P-B7C22A9P						
	2711-B6C14L1					2711P-B7C22D9P						
	2711-B6C12				RS-232	2711P-B7C22A9P						
	2711-B6C12L1					2711P-B7C22D9P						
	2711-B6C16				RS-232 (DF1)	2711P-B7C22A9P						
	2711-B6C16L1					2711P-B7C22D9P						

PanelView Standard 600 Terminals Secondary Replacement Options

PanelView Standard Terminals						PanelView Plus 7 Terminals – Secondary Replacement Options						
Model	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Cat. No.	Panel Cutout Dimensions		Display Resolution	Comm.	Adapter Plate Cat. No.	Notes
		Height mm (in.)	Width mm (in.)				Height mm (in.)	Width mm (in.)				
600	2711-K6C1	192 (7.55)	290 (11.40)	320 x 234	Remote I/O	2711P-T7C21D8S	142 (5.59)	184 (7.24)	640 x 480	One Ethernet port	N/A	PanelView Plus 7 Standard 6.5-in. terminal benefits: Higher resolution Application limits: • Max. screen count: 25 • Max. alarm messages: 200 • Max. number of controllers: 1 Communication = Ethernet (dual Ethernet ports are available). Operator input = only touch. Power input = only DC. Conformal coat = No.
	2711-K6C1L1				DeviceNet							
	2711-K6C10											
	2711-K6C10L1											
	2711-K6C14											
	2711-K6C14L1				RS-232							
	2711-K6C12											
	2711-K6C12L1				RS-232 (DF1)							
	2711-K6C16											
	2711-K6C16L1				ControlNet							
	2711-K6C15											
	2711-K6C15L1				DH-485							
	2711-K6C2											
	2711-K6C2L1											
	2711-K6C3											
	2711-K6C3L1				RS-232 (DH-485)							
	2711-K6C5											
	2711-K6C5L1				DH+							
	2711-K6C9											
	2711-K6C9L1											
	2711-K6C8											
	2711-K6C8L1				EtherNet/IP							
	2711-K6C20											
	2711-K6C20L1				Remote I/O							
	2711-B6C1											
	2711-B6C1L1				DeviceNet							
	2711-B6C10											
	2711-B6C10L1											
	2711-B6C14											
	2711-B6C14L1				RS-232							
	2711-B6C12											
	2711-B6C12L1				RS-232 (DF1)							
	2711-B6C16											
	2711-B6C16L1											