

*** SPARE PART*** OP 3 OPERATOR PANEL WITH CABLE FOR CONNECTION TO SIMATIC S7, SER. CABLE FOR CONFIGURING AND CABLE FOR POWER SUPPLY



General information

Customer-specific configuration	No
---------------------------------	----

Display

Design of display	LC display
graphics-enabled	No
Color type	Black/white

Line display

• Number of lines	2
• Number of characters per line	20

Backlighting

• MTBF backlighting (at 25 °C)	200 000 h
--------------------------------	-----------

Control elements

Control elements	Keys
------------------	------

Keyboard fonts

• Membrane keyboard	Yes
— user-definable label membrane keys	No
• Function keys	
— Number of function keys	5

- Numeric/alphabetical input — hexadecimal keyboard - Multi-key operation	Yes / No No No
Touch operation	
Design as touch screen	No
Connection type	
Connection for mouse/keyboard/barcode reader	- / - / -
Installation type/mounting	
Mounting position	vertical
maximum permissible angle of inclination without external ventilation	180°
Supply voltage	
Type of supply voltage	24 V DC
UPS connectable (serial)	No
Input current	
Current consumption (rated value)	0.07 A
Processor	
Processor type	X86
Drives	
Diskette drive	No
CD-ROM	No
Hard disk	No
Memory	
Type of memory	Flash / RAM
Memory available for user data	128 kbyte
Battery	
Backup battery	
- Backup battery - Backup time, min.	No 0 y
Time of day	
Clock	
- Type - retentive - synchronizable	Software clock, no battery backup No No
Interfaces	
Interfaces/bus type	1 x RS232, 1 x RS485 (max. 1.5 Mbit/s)
Number of RS 485 interfaces	1
Transmission rate, max.	1.5 Mbit/s

Number of parallel interfaces	0
USB port	No
PC card slot	No
CF card slot	No
Special interfaces	No
With software interfaces	No
Industrial Ethernet	
• Industrial Ethernet interface	No
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
Standards, approvals, certificates	
Certifications	CE, GL, DNV, LRS, PRS, FM Class I Div. 2, UL, CSA, cULus
Ambient conditions	
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	85 %
Operating systems	
pre-installed operating system	Rmos
Configuration	
Message indicator	Yes
Alarm system (incl. buffer and acknowledgment)	No
Process value display (output)	No
Process value default (input) possible	No
Recipe management	No
Configuration software	
• Configuration tool	ProTool / Lite Version 2.51 or higher (to be ordered separately)
Peripherals/Options	
Additional software components loadable	No
Dimensions	
Width of the housing front	148 mm
Height of housing front	76 mm
Overall depth	25 mm
Weights	
Weight (without packaging)	0.25 kg
Other	
free hotline	Yes

Warranty period

1 y

last modified:

04/24/2017 