1756-L65

Allen-Bradley ControlLogix 5560 / ControlLogix 5565

Official-source technical excerpt

Product Identification

Complete catalog number	1756-L65
Brand	Allen-Bradley / Rockwell Automation
Product family	ControlLogix 5560 / ControlLogix 5565
Product description	ControlLogix 32 MB Memory Controller
Series	B
Data and logic memory	32 MB
I/O memory	478 KB
Minimum firmware	Revision 17 or later
Nonvolatile memory	Optional Industrial CompactFlash card
Lifecycle	Discontinued June 1, 2017

Technical and Environmental Data

Interface	Front-panel RS-232 serial port
Backplane current	1.20 A at 5.1 V DC; 14 mA at 24 V DC
Power dissipation	3.5 W
Thermal dissipation	11.9 BTU per hour
Weight	Approximately 0.35 kg (12.4 oz)
Dimensions	Not explicitly stated for 1756-L65 in publication 1756-IN101F-EN-P
Operating temperature	0 to +60 degrees C
Storage temperature	-40 to +85 degrees C
Relative humidity	5 to 95 percent, noncondensing

Official Document References

Rockwell Automation publication **1756-IN101F-EN-P**, relevant printed pages **8, 16 and 41-48**, and the official 1756-L65 product page were used for this exact-model excerpt.

Official PDF: https://literature.rockwellautomation.com/idc/groups/literature/documents/in/1756-in101_-en-p.pdf

Official product page: https://www.rockwellautomation.com/en-us/products/details.1756-L65.html

This concise official-source excerpt is for 1756-L65 and does not replace the complete Rockwell Automation publication or product label.