

Product type designation

IE/PB LINK PN IO
IE/PB LINK PN IO gateway between Ind. Ethernet and PROFIBUS with PROFINET IO Functionality S7 routing and data record routing, 10/100 Mbit/s Fast Ethernet, MRP, 9.6 kbit/s up to 12 Mbit/s PROFIBUS, NTP.



Transmission rate	
Transfer rate	
• for Industrial Ethernet	10 ... 100 Mbit/s
• at the 1st interface / acc. to PROFIBUS	9.6 kbit/s ... 12 Mbit/s
Interfaces	
Number of interfaces / acc. to Industrial Ethernet	1
Number of electrical connections	
• at the 1st interface / acc. to Industrial Ethernet	2
• at the 1st interface / acc. to PROFIBUS	1
• for power supply	2
Type of electrical connection	
• at the 1st interface / acc. to PROFIBUS	9-pin Sub-D socket (RS485)
• at the 1st interface / acc. to Industrial Ethernet	RJ45 port
• for power supply	4-pole terminal block
design of the removable storage / C-PLUG	Yes
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC

Supply voltage / external	24 V
Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	15 %
Consumed current	
• from external supply voltage / at DC / at 24 V / typical	0.2 A
• from external supply voltage / at DC / at 24 V / maximum	0.3 A
Power loss [W]	4.8 W

Permitted ambient conditions

Ambient temperature	
• for vertical installation / during operation	0 ... 40 °C
• for horizontally arranged busbars / during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Width	100 mm
Height	117 mm
Depth	74 mm
Net weight	0.6 kg
Mounting type	
• 35 mm DIN rail mounting	Yes

Performance data / PROFIBUS DP

Service / as DP master	
• DPV1	Yes
Number of DP slaves / on DP master / usable	65
Amount of data	
• of the address area of the inputs / as DP master / total	2048 byte
• of the address area of the outputs / as DP master / total	2048 byte
• of the address area of the inputs / per DP slave	244 byte
• of the address area of the outputs / per DP slave	244 byte

Performance data / S7 communication

Number of possible connections / for S7 communication	
---	--

- maximum

32

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	48
---	----

Performance data / PROFINET communication / as PN IO-Device

Product function / PROFINET IO device	Yes
---------------------------------------	-----

Performance data / telecontrol

Protocol / is supported	
-------------------------	--

- TCP/IP
- Yes

Product function / MIB support	Yes
--------------------------------	-----

Protocol / is supported	
-------------------------	--

- SNMP v1
- Yes

- DCP
- Yes

- LLDP
- Yes

Identification & maintenance function	
---------------------------------------	--

- I&M0 - device-specific information
- Yes

- I&M1 – higher-level designation/location designation
- Yes

- I&M3 - comment
- Yes

Product functions / switch

Product feature / Switch	Yes
--------------------------	-----

Product function	
------------------	--

- Configuration with STEP 7
- Yes

Product functions / Routing

Service / as PROFIBUS / dataset routing	Yes
---	-----

Number of possible connections / with dataset routing / maximum	32
---	----

Product functions / Redundancy

Product function	
------------------	--

- Ring redundancy
- Yes

Protocol / is supported / Media Redundancy Protocol (MRP)	Yes
---	-----

Product functions / Time

Product function / SICLOCK support	Yes
------------------------------------	-----

Product function / pass on time synchronization	Yes
---	-----

Protocol / is supported	
-------------------------	--

- NTP
- Yes

Accessories

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

Security information

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
----------------------	--

last modified:

04/16/2018 