Allen-Bradley ControlLogix 5580

1756-L85EP - 40 MB EtherNet/IP Process Controller

Official product description: ControlLogix 5580E process controller with 40 MB user memory, USB port, one 1 Gb EtherNet/IP port, capacity for 300 EtherNet/IP devices and a four-character alphanumeric display.

CORE FEATURE	40 MB user memory with embedded 1 Gb EtherNet/IP networking.	**LEAD TIME: In stock**	**WARRANTY: 1 year**

Technical Data

Complete model	1756-L85EP
Product family	ControlLogix 5580
Product type	ControlLogix 5580E process controller
Memory	40 MB user memory
I/O capacity	128,000 digital I/O maximum; 4,000 analog I/O maximum
Nonvolatile storage	4 GB 1784-SD4 Secure Digital card, preinstalled
Interfaces	One embedded 10/100/1000 Mbps EtherNet/IP port; USB 2.0 local programming port
EtherNet/IP capacity	300 EtherNet/IP devices
Current draw	5.0 mA at 1.2 V DC; 1.20 A at 5.1 V DC
Power / thermal	6.2 W; 21.2 BTU per hour
Dimensions	34.55 x 145.2 x 139.6 mm, width x height x depth
Weight	Approximately 0.394 kg (0.868 lb)
Mounting	One slot in a compatible 1756 chassis
Operating temperature	-25 to +70 C in compatible XT Series C or ZXT chassis; -25 to +60 C in standard Series C; -25 to +50 C in standard Series B
Storage / humidity	-40 to +85 C; 5 to 95 percent RH, noncondensing
Coating / enclosure	Conformal coated; open-style equipment
Certifications	c-UL-us, FM, CE, RCM, ATEX, IECEx, UKEx and UKCA as marked

Official References

Technical Data 1756-TD001W-EN-P, pages 26-29; Installation Instructions 1756-IN043G-EN-P, pages 5-9.
Product page: https://www.rockwellautomation.com/en-us/products/details.1756-L85EP.html
Technical Data: https://literature.rockwellautomation.com/idc/groups/literature/documents/td/1756-td001_-en-p.pdf
Installation Instructions: https://literature.rockwellautomation.com/idc/groups/literature/documents/in/1756-in043_-en-p.pdf