SIEMENS

数据页 **6ED1055-4MH08-0BA1**

LOGO! TDE 文本显示， 6 行，3 种背景颜色， 2 个以太网接口， 用于 LOGO! 8



□□□□

一般信息	
产品类型标志	纯文本显示屏
适用性	自 LOGO 开始可用！ 8
显示	
显示屏规格	FSTN
逐行显示	
● 行数	6
● 每行的字符数	20
背光灯	
● 背光类型	LED
操作元件	
键盘	
● 系统按键	是
— 可组态的系统按键	0
● 字母数字键盘	否
安装方式/安装	
壁板安装/直接安装	否
电源电压	
电源的电压类型	AC/DC
额定值 (DC)	12 V; 12/24 V DC，24 V AC
功率损失	
功率损失，典型值	1.8 W; 24 V DC 时
报警/诊断/状态信息	
诊断功能	否
防护等级和防护类别	
IP（正面）	IP65
标准、许可、证书	
CE 标记	是
UL 许可	是
FM 许可	是
KC 许可	是
生态足迹	
● 环境产品声明	是
减排潜力	
— 减排潜力，（总计）[碳足迹]	43 kg
— 减排潜力，（生产过程中）[碳足迹]	8.5 kg

保留变更权利
© Copyright Siemens

— 减排潜力，（运营过程中）[碳足迹]	34.5 kg
— 减排潜力，（生命周期结束之后）[碳足迹]	-0.065 kg
船舶建造许可	
● 美国船舶检验局 (ABS)	是
环境要求	
运行中的环境温度	
● 最小值	-20 °C; 无凝露
● 最大值	55 °C
运输/储存时的环境温度	
● 最小值	-40 °C
● 最大值	70 °C
参考海平面的运行高度	
● 环境温度-气压-安装高度	1 080 hPa ... 795 hPa 时 Tmin ... Tmax (-1 000 m ... +2 000 m)
组态	
组态软件	
● 组态工具	LOGO! Soft Comfort V8
附件	
属于产品	LOGO!
机械/材料	
壳体规格	塑料
尺寸	
宽度	128.2 mm
高度	86 mm
深度	38.7 mm
安装深度	38.7 mm
重量	
重量，约	220 g
分类	

	版本	分类
eClass	16	27-33-02-03
eClass	14	27-33-02-03
eClass	12	27-33-02-03
eClass	9.1	27-33-02-03
eClass	9	27-33-02-03
eClass	8	27-24-23-04
eClass	7.1	27-24-23-04
eClass	6	27-24-23-04
ETIM	10	EC001426
ETIM	9	EC001426
ETIM	8	EC001426
ETIM	7	EC001426
IDEA	4	6679
UNSPSC	15	43-21-19-06

认可 / 证书

General Product Approval

Miscellaneous

Metrological Approval

General Product Approval

保留变更权利
© Copyright Siemens

China RoHS

General Product Approval	EMV	For use in hazardous locations			
Manufacturer Declaration		CCC-Ex		FM	CCC-Ex

Maritime application					
				NK / Nippon Kaiji Kyokai	CCS (China Classification Society)

Maritime application	Environment
KR (Korean Register of Shipping)	

上一次修改： 2025/7/2

保留变更权利
© Copyright Siemens