



SIMATIC DP, 5 electronic modules for ET 200S, 2 DI High Feature 24 V DC, 15 mm width, with param. input delay Diagnostics encoder short circuit with SF LED (group fault) 5 units per packing unit

Supply voltage	
Rated value (DC)	24 V; From power module
Reverse polarity protection	Yes
Input current	
from supply voltage L+, max.	Dependent on encoder
from backplane bus 3.3 V DC, max.	10 mA
Encoder supply	
Type of output voltage	min. L+ (-0.5 V), under load
Short-circuit protection	Yes; Electronic
Output current	
- Rated value - permissible range, lower limit - permissible range, upper limit	500 mA 0 mA 500 mA
Power loss	
Power loss, typ.	0.4 W
Address area	
Address space per module	
- Address space per module, max. - with packing	1 byte 2 bit
Digital inputs	
Number of digital inputs	2
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
- Type of input voltage - Rated value (DC) - for signal "0" - for signal "1"	DC 24 V -30 to +5 V +11 to +30V
Input current	
for signal "1", typ.	8 mA
Input delay (for rated value of input voltage)	
for standard inputs	
- parameterizable - at "0" to "1", min. - at "0" to "1", max. - at "1" to "0", min. - at "1" to "0", max.	Yes; 0.1 / 0.5 / 3 / 15 ms 0.05 / 0.4 / 2.7 / 14.85 0.15 / 0.6 / 3.3 / 15.15 0.05 / 0.4 / 2.7 / 14.85 0.15 / 0.6 / 3.3 / 15.15
Cable length	
shielded, max.	1 000 m

• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Hardware interrupt	Yes; Parameterizable
Diagnoses	
• Short-circuit	Yes; Short-circuit of outputs to ground; module by module
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes; per channel
Parameter	
Remark	3 byte
Diagnostics short-circuit	Disable / enable
Potential separation	
Potential separation digital inputs	
• between the channels	No
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	35 g
last modified:	2/9/2021 