SIEMENS

Data sheet 6GK5216-0BA00-2AA3



- - spare part - - SCALANCE X216, managed IE switch, 16x 10/100 Mbps RJ45 ports, LED diagnostics, error-signaling contact with set pushbutton, redundant power supply, PROFINET IO device, network management, redundancy manager integrated, including electronic manual on CD-ROM, C-PLUG optional.

product type designation	
product brand name	SCALANCE
product type designation	X216
transfer rate	
transfer rate	10, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
● for network components or terminal equipment	16
number of 10/100 Mbit/s RJ45 ports	
● with securing collar	16
interfaces / other	
number of electrical connections	
● for signaling contact	1
● for power supply	1
type of electrical connection	
● for signaling contact	2-pole terminal block
● for power supply	4-pole terminal block
design of the removable storage	
● C-PLUG	Yes
operating voltage / of the signaling contacts	
● at DC / rated value	24 V
operational current / of the signaling contacts	
● at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
● supply voltage / 1 / rated value	24 V
● power loss [W] / 1 / rated value	5.76 W
● consumed current / 1 / maximum	0.24 A
● type of electrical connection / 1 / for power supply	4-pole terminal block
● product component / 1 / fusing at power supply input	Yes
● fuse protection type / 1 / at input for supply voltage	1,1 A / 33 V
ambient conditions	
ambient temperature	
● during operation	-40 ... +60 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
relative humidity	
● at 25 °C / without condensation / during operation /	95 %

Subject to change without notice
© Copyright Siemens

maximum	
protection class IP	IP30
design, dimensions and weights	
design	compact
width	120 mm
height	125 mm
depth	124 mm
net weight	1.2 kg
fastening method	
● 35 mm DIN-rail mounting	Yes
● wall mounting	Yes
● S7-300 rail mounting	Yes
● S7-1500 rail mounting	No
product features, product functions, product components / general	
cascading in the case of a redundant ring / at reconfiguration time of <\~0.3\~s	100
cascading in cases of star topology	any (depending only on signal propagation time)
product functions / management, configuration, engineering	
product function	
● CLI	Yes
● web-based management	Yes
● MIB support	Yes
● TRAPs via email	Yes
● configuration with STEP 7	Yes
● port mirroring	Yes
● multiport mirroring	No
● with IRT / PROFINET IO switch	No
● PROFINET IO diagnosis	Yes
● switch-managed	Yes
PROFINET conformity class	B
protocol / is supported	
● Telnet	Yes
● HTTP	Yes
● HTTPS	Yes
● TFTP	Yes
● FTP	Yes
● BOOTP	No
● DCP	Yes
● LLDP	Yes
● SNMP v1	Yes
● SNMP v2	Yes
● SNMP v3	Yes
identification & maintenance function	
● I&M0 - device-specific information	Yes
● I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function	
● port diagnostics	Yes
● statistics Packet Size	Yes
● statistics packet type	Yes
● error statistics	Yes
product functions / VLAN	
number of VLANs / at ring redundancy (HRP; MRP; standby link)	257
product functions / DHCP	
product function	
● DHCP client	Yes
product functions / redundancy	
protocol / is supported / Media Redundancy Protocol (MRP)	Yes

Subject to change without notice
© Copyright Siemens

product function	
● media redundancy protocol (MRP) with redundancy manager	Yes
● ring redundancy	Yes
● high speed redundancy protocol (HRP) with redundancy manager	Yes
● high speed redundancy protocol (HRP) with standby redundancy	No
● Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
● Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
● passive listening	Yes
product functions / security	
protocol / is supported	
● SSH	Yes
product functions / time	
product function	
● SICLOCK support	Yes
protocol / is supported	
● NTP	No
● SNTP	Yes
standards, specifications, approvals	
certificate of suitability	
● CE marking	Yes
● KC approval	Yes
● Regulatory Compliance Mark (RCM)	Yes
standard	
● for EMC interference emission	EN 61000-6-4:2001 (Class A)
● for immunity to EMC	EN 61000-6-2:2001
● for safety / from CSA and UL	UL 60950-1 E115352, CSA C22.2 No. 60950-1
standards, specifications, approvals / hazardous environments	
certificate of suitability	
● ATEX	Yes
● IECEx	Yes
● ULhazloc approval	Yes
● CCC / for hazardous zone according to GB standard	Yes
● FM registration	Yes
standards, specifications, approvals / other	
certificate of suitability	
● railway application in accordance with EN 50155	No
● railway application in accordance with EN 50124-1	No
● RoHS conformity	Yes
standards, specifications, approvals / marine classification	
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	Yes
● French marine classification society (BV)	Yes
● Lloyds Register of Shipping (LRS)	Yes
● Nippon Kaiji Kyokai (NK)	Yes
● Polski Rejestr Statkow (PRS)	Yes
● Royal Institution of Naval Architects (RINA)	Yes
product functions / general	
MTBF	52.07 a
warranty period	5 a
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com/

Subject to change without notice
© Copyright Siemens

● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval

Declaration of Conformity | China RoHS | Manufacturer Declaration

General Product Approval | EMV

China RoHS

For use in hazardous locations | Test Certificates | Maritime application

FM | CCC-Ex | Type Test Certificates/Test Report

Maritime application

NK / Nippon Kaiji Kyokai

Industrial Communication

PROFINET

last modified: 3/10/2026

Subject to change without notice
© Copyright Siemens