



Figure similar

*** Spare part *** SIMATIC DP, Electronics module for ET 200S, 2 pulses Pulse generator and timer module, 15 mm wide, 2 channels


Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V; From power module
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	40 mA
from backplane bus 3.3 V DC, max.	10 mA
Encoder supply	
Type of output voltage	L+ (-0.8 V)
Short-circuit protection	Yes
Output current	
• Rated value	500 mA
Power loss	
Power loss, typ.	1.8 W
Digital inputs	
Number of digital inputs	2
Input characteristic curve in accordance with IEC 61131, type 2	Yes
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	+11 to +30V
Input current	
• for signal "1", typ.	9 mA
Input delay (for rated value of input voltage)	
• Input frequency (with a time delay of 0.1 ms), max.	20 kHz
• Minimum pulse width for program reactions	100 µs
Cable length	
• shielded, max.	100 m
Digital outputs	
Number of digital outputs	2
Short-circuit protection	Yes
• Response threshold, typ.	10 A
Limitation of inductive shutdown voltage to	L+ (-50 to -65 V)
Controlling a digital input	Yes
Accuracy of pulse duration	±(time period x 100 ppm), ±100 µs with a load ≤ 50 ohms
minimum pulse duration	100 µs
Switching capacity of the outputs	
• on lamp load, max.	10 W

Output voltage			
• for signal "1", min.	L+ (-1 V)		
Output current			
• for signal "1" rated value	2 A		
• for signal "1" permissible range for 0 to 60 °C, min.	7 mA		
• for signal "1" permissible range for 0 to 60 °C, max.	2 A		
• for signal "0" residual current, max.	0.5 mA		
Output delay with resistive load			
• "0" to "1", max.	100 µs		
• "1" to "0", max.	200 µs		
Switching frequency			
• with resistive load, max.	5 kHz		
• with inductive load, max.	2 Hz		
• on lamp load, max.	10 Hz		
Cable length			
• shielded, max.	1 000 m		
• unshielded, max.	600 m		
Encoder			
Connectable encoders			
• 2-wire sensor	Yes		
— permissible quiescent current (2-wire sensor), max.	2 mA		
Interrupts/diagnostics/status information			
Diagnostics indication LED			
• Group error SF (red)	Yes		
• Status indicator digital input (green)	Yes		
• Status indicator digital output (green)	Yes		
Integrated Functions			
Pulse generator			
• Number of channels	2; 1 digital input and 1 digital output per channel		
Potential separation			
Potential separation digital inputs			
• between the channels	No		
• between the channels and backplane bus	Yes		
Potential separation digital outputs			
• between the channels	No		
• between the channels and backplane bus	Yes		
Isolation			
Isolation tested with	500 V DC		
Dimensions			
Width	15 mm		
Height	81 mm		
Depth	52 mm		
Weights			
Weight, approx.	40 g		
Classifications			
		Version	Classification
	eClass	16	27-24-26-05
	eClass	14	27-24-26-05
	eClass	12	27-24-26-05
	eClass	9.1	27-24-26-05
	eClass	9	27-24-26-05
	eClass	8	27-24-26-05
	eClass	7.1	27-24-26-05
	eClass	6	27-24-26-05
	ETIM	10	EC001601
	ETIM	9	EC001601

ETIM	8	EC001601
ETIM	7	EC001601
IDEA	4	3567
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval




General Product Approval

EMV

For use in hazardous locations



For use in hazardous locations




For use in hazardous locations

Maritime application



Maritime application



last modified:

7/3/2026