

Catalogue No: **6181F-15TSXP**

1500P PC WINXP PRO 15in TOUCH 16GB SSD 2GB RAM AC

Automation Systems > Operator Panels and Industrial Computers > Industrial Computers > Allen-Bradley® Industrial Computers > Integrated Display Computers > 15" Touchscreen Display



Representative Photo Only
(actual product may vary based on configuration selections)

1500P PC WINXP PRO 15in TOUCH 16GB SSD 2GB RAM AC

- Industrial Environment Computers offer solutions for the physical limitations and requirements of your environment.
- Non-display Computers provide a variety of options in form factors, RAM, storage, performance, operating temperatures and optical drives.
- Integrated Display Computers are available in different screen sizes, storage options, performance packages, and models with built-in keypads.

SPECIFICATIONS

Product Series	6181P
Power Supply	100/240V AC
Power Consumption (Max.)	100 W(DC) / VA(AC)
Component Type Ind. Computer	Integrated Display Industrial Computer
Operating System	Windows XP Pro
Processor / CPU	Intel Celeron 1.06 GHz
Chipset	Intel 945GME + ICH7-M
RAM, Installed	2 GB
RAM, Maximum	4 GB
RAM Type	DDR2 SO-DIMM Dual-Channel
Storage Type	2.5" SATA SSD
Storage Size	32 GB
Memory Card Slots	1 x CFast Slot external access, Type 2 (bootable)
Operator Input Method(s)	Touch
Display Size	15 inches
Display Technology	LCD, TFT (Thin Film Transistor)
Display Resolution	1024x768 pixels
Display Colours	16700 k
Touch Screen Type	Resistive, 5 wires
Material, Bezel	Aluminium
Ethernet Interfaces	2 x 10/100/1000Mbps
Peripheral I/O Interface(s)	5 x USB 2.0 1 x Mic IN + Audio Line IN/OUT
IP Rating, Front	IP66
Height, Cutout	285 mm
Width, Cutout	386.6 mm
Operating Temperature, Max	55 °C max
Operating Temperature, Min	0 °C min

Catalogue No: **6181F-15TSXP**
1500P PC WINXP PRO 15in TOUCH 16GB SSD 2GB RAM AC

Automation Systems > Operator Panels and Industrial Computers > Industrial Computers > Allen-Bradley® Industrial Computers > Integrated Display Computers > 15" Touchscreen Display



Storage Temperature, Max	60 °C max
Storage Temperature, Min	-20 °C min
Relative Humidity, Max	90 %RH

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-