

Product type designation

RF170C communication module
RFID



Suitability for operation

Dezentrale Peripherie ET 200pro together with RF200/300/600, MV400, MOBY D/E/I/U

Transmission rate

Transfer rate / at the point-to-point connection / serial / maximum 115.2 kbit/s

Interfaces

Design of the interface / for point-to-point connection RS422 via connection block

Number of readers / connectable 2

Type of electrical connection

- of the backplane bus ET 200pro backplane bus
- of the PROFIBUS interface (according to the head module)
- of Industrial Ethernet interface (according to the head module)
- for supply voltage ET 200pro backplane bus

Design of the interface / to the reader / for communication Internal plug to the connection block

Mechanical data

Material Thermoplastic (Valox 467, fiberglass reinforced)

Color IP Basic 714

Tightening torque / of the screw for securing the equipment / maximum	1.5 N·m
Supply voltage, current consumption, power loss	
Supply voltage	
• at DC / Rated value	24 V
• at DC	20 ... 30 V
Consumed current / at DC / at 24 V	
• without connected devices / typical	0.13 A
• with connected devices / maximum	1 A
Permitted ambient conditions	
Ambient temperature	
• during operation	-25 ... +55 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Protection class IP	IP67
Shock resistance	According to IEC 61131-2
Shock acceleration	300 m/s ²
Vibrational acceleration	100 m/s ²
Design, dimensions and weight	
Width	90 mm
Height	130 mm
Depth	35 mm
Net weight	0.27 kg
Mounting type	ET 200pro rack
Wire length / for RS 422 interface / maximum	1000 m
Product properties, functions, components / general	
Display version	(see connection block)
Product function / transponder file handler can be addressed	No
Protocol / is supported	
• S7 communication	Yes
Type of parameterization	HSP
Type of programming	FB 45, FB 55 (FC 45/55 with limited functionality)
Type of computer-mediated communication	acyclic communication
Standards, specifications, approvals	
Certificate of suitability	CE, FCC, cULus
MTBF	129 y
Accessories	
accessories	Connection block for RF170C
Further Information / Internet Links	

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

Security information	
----------------------	--

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
----------------------	--

last modified:

06/10/2017 