Bulletin No.	**2711P**	**2711P**	**2711P**
Type	**PanelView Plus 400**	**PanelView Plus 600 Grayscale**	**PanelView Plus 600 Colour**
Display			
Type	Monochrome Passive Matrix, Film Compensated Super-Twist Nematic (FSTN)		
Size	78 x 59 mm (3.7 in)	111 x 84 mm (5.5 in)	111 x 84 mm (5.5 in)
Resolution	320 x 240, 32 level, grayscale		320 x 240, 18 bit colour graphics
Replaceable Backlight	No	No	No
Operator Input	Keypad	Keypad, Analog Touch, or Combination	Keypad, Analog Touch, or Combination
Function Keys	8 Function Keys, F1-F8	10 Function Keys, F1-F10	10 Function Keys, F1-F10
Real time Clock	Battery-backed time clock timestamps critical data. Accuracy +/-2 minutes per month		
Memory Options Available Flash/RAM	Standard 32 MB/64 MB, Not Expandable		
Electrical			
Communication Port	RS-232 and (1) USB Only or Ethernet, RS-232, (1) USB, plus optional DH-485, DH+, or Remote I/O modules		
Power Requirements	18-32V DC or 85-264V AC @ 47-63 Hz		
Power Consumption	DC Power: 25 Watts max. (1.0A @ 24V DC) AC Power: 60VA max.		
Programming	RSView Studio for Machine Edition or Enterprise Series		
Environmental			
Operating Temperature	0 - 55°C		
Storage Temperature	-25 – 70°C		
Humidity	5 - 95%, noncondensing @ 0 - 55°C		
Ratings	NEMA 12, 13 4X, IP54, IP65		
Certifications	cUL certified; UL listed; Class 1, Div 2, Groups A, B, C, D; Class 2, Div 2, Groups F, G; Class 3, Div 1; CE marked; C-Tick		
Mechanical			
Weight Keypad or Keypad/Touch	0.562 kg	0.789 kg	0.789 kg
Weight Touch Only	N/A	0.789kg	0.789kg
Dimensions Overall (H x W x D)	Keypad: 152x185x90 mm	Keypad or Keypad/Touch: 167x266x98 mm Touch Only: 152x185x98mm	
Cutout Dimensions	Keypad: 123x156 mm	Keypad or Keypad/Touch: 142x241 mm Touch Only: 123x156 mm	
Page Number	**Page 194, 197**	**Page 195, 197**	**Page 196, 197**

- 320 x 240, 18 bit colour graphics
- 10 Function Keys
- Operator Input: Keypad, Analog Touch, or Combination
- 32 MB/64 MB Memory

PanelView Plus 600 Colour

Description	Interface	Supply	Cat. No.	PQ
Keypad	RS232 Only	DC Power	2711P-K6C5D	1
		AC Power	2711P-K6C5A	
	Ethernet, RS232, and Modular Communication Interface	DC Power	2711P-K6C20D	
		AC Power	2711P-K6C20A	
	Ethernet, RS232, and DH485 Modular Communications	DC Power	2711P-K6C3D	
		AC Power	2711P-K6C3A	
	Ethernet, RS232, & DH+ Modular Communications	DC Power	2711P-K6C8D	
		AC Power	2711P-K6C8A	
	Ethernet, RS232, & RIO Modular Communications	DC Power	2711P-K6C1D	
		AC Power	2711P-K6C1A	
Touch	RS232 Only	DC Power	2711P-T6C5D	1
		AC Power	2711P-T6C5A	
	Ethernet, RS232, and Modular Communication Interface	DC Power	2711P-T6C20D	
		AC Power	2711P-T6C20A	
	Ethernet, RS232, and DH485 Modular Communications	DC Power	2711P-T6C3D	
		AC Power	2711P-T6C3A	
	Ethernet, RS232, & DH+ Modular Communications	DC Power	2711P-T6C8D	
		AC Power	2711P-T6C8A	
	Ethernet, RS232, & RIO Modular Communications	DC Power	2711P-T6C1D	
		AC Power	2711P-T6C1A	
Keypad/Touch	RS232 Only	DC Power	2711P-B6C5D	1
		AC Power	2711P-B6C5A	
	Ethernet, RS232, and Modular Communication Interface	DC Power	2711P-B6C20D	
		AC Power	2711P-B6C20A	
	Ethernet, RS232, and DH485 Modular Communications	DC Power	2711P-B6C3D	
		AC Power	2711P-B6C3A	
	Ethernet, RS232, & DH+ Modular Communications	DC Power	2711P-B6C8D	
		AC Power	2711P-B6C8A	
	Ethernet, RS232, & RIO Modular Communications	DC Power	2711P-B6C1D	
		AC Power	2711P-B6C1A	

Accessories for PanelView Plus 600 see Page 197

PQ = Package Quantity