

8mm Eddy Current Sensor




Non-contact sensor designed for critical turbomachinery applications such as steam, gas and hydro turbines, compressors, gearboxes, pumps and fans to measure radial and axial shaft dynamic displacement; position, eccentricity and speed.



Performance	
Linear Measurement Range	2 mm (80 mils)
Initial Air Gap	0.5 mm (20 mils)
Incremental Scale Factor (ISF)	ISO: 8 V/mm (203.2 mV/mil) ± 5% @ temperature range 0 to 45°C (+32 to +113°F)
Deviation from best fit straight line (DSL)	± 0.025 mm (± 1 mil) @ temperature range 0 to 45°C (+32 to +113°F)
Measuring Target	
Minimum Shaft Diameter	25 mm (0.79”)
Target Material (Ferromagnetic Steel)	42CrMo4 (AISI/SAE 4140) Standard Other (On Request)
Environmental, General	
Protection Class	IP66, IEC 60529
Operating Temperature Range	Sensor incl. 1m Cable: -35 to +180°C (-31 to 356°F) Cable & Connector: -35 to +150°C (-31 to 302°F)
Material	Sensor Tip (PEEK Polyether Ether Ketone), Case (Stainless Steel) Cable (PTFE Polytetrafluoroethylene), Connector (Brass, nickel-plated)
Weight (Sensor with 1m Cable)	Approx. 100 grams (3.53 oz)

Dimensions

PR6423/xxx-xxx (Standard)



A. Case thread, M10x1 or 3/8-24UNF
B. SW 11 mm for M10 threads, SW 7/9-16 in for 3/8-24UNF threads
C. Standard cable diameter 2.8 mm (0.110 in), minimum bending radius 25 mm (0.984 in)
D. Armored cable diameter 6 mm (0.236 in), minimum bending radius 35 mm (1.378 in)
E. Optional Adapter Plug after 1m cable from Sensor
F. Cable Length (Tolerances 0... +10%)
G. Lemo connector (male), 11.0 mm (0.433 in) diameter or open cable end

Ordering Information

Tip Diameter	Case Threads	Armored Cable	Model No.
8mm	M10x1	No	PR6423/00
		Yes	PR6423/01
			PR6423/03*
	3/8"-24 UNF	No	PR6423/10
		Yes	PR6423/11
			PR6423/13*

**Armored cable option for Reverse Mount, if Adapter Plug is chosen.*

Model No.	Case Thread X	Adapter Plug X	Cable Length X	Cable End X
PR6423/00 PR6423/01 PR6423/10 PR6423/11	**0** 25mm **1** 35mm **2** 45mm **3** 55mm **4** 65mm **5** 75mm **6** 85mm **7** 95mm **8** 105mm **9** 115mm **E** 155mm **H** 195mm **R** Reverse Mount	**0** With **1** Without	**0** 4.0m **1** 5.0m **3** 8.0m **F** 9.0m **4** 10.0m	**0** Lemo* **1** Open

**Not available, if Reverse Mount without Adapter Plug is chosen.*

Example: PR6423/000-000


ECS 8mm, M10X1, NO ARMOR, 25MM SLEEVE, 1+3M CABLE, LEMO


Eddy Current Signal Converter

Sensor Signal Converter designed for critical turbo machinery applications such as steam, gas and hydro turbines, compressors, pumps and fans to measure radial and axial shaft displacement, position, eccentricity and speed/key.



Dynamic Performance	
Frequency Range (-3 dB)	0 to 20000 Hz
Rise Time	<15 µs
NOTE: Designed for PR6422, PR6423, PR6424, PR6425, PR6426, PR 6453 For extended range use: CON021/91x-xxx PR6425 always requires extended range converter	
Environmental	
Operating Temperature Range	-30 to 100°C (-22 to 212°F)
Shock and Vibration	5g @ 60 Hz @ 25°C (77°F)
Protection Class	IP20
Power & Electrical	
Supply Voltage Range	-23V to -32V (Output Range -4V to -20V)
	-21V to -32V (Output Range -2V to -18V)
Physical	
Housing Material	LMgSi 0.5 F22
Weight	~120 grams (4.24 oz)
Mounting	4 Screws M5x20 (Included in Delivery)
Connections: Transduer	Self-Locking Lemo-Plug
Supply/Output	Screw Terminal Type (max.1.5mm², wire)





Ordering Information

Model Number	Sensor Type	Measuring Range	Linearity Error
CON021	PR6422 PR6423 PR6424 PR6426	1.0mm (Standard Range) 2.0mm (Standard Range) 4.0mm (Standard Range) 8.0mm (Standard Range)	≤ 1.5% ≤ 1.0% ≤ 1.5% ≤ 1.5%
CON021/912-015	PR6422	1.5mm (Extended Range)	≤ 2.0%
CON021/913-030	PR6423	3.0mm (Extended Range)	≤ 1.5%
CON021/913-040	PR6423	4.0mm (Extended Range)	≤ 2.0%
CON021/914-060	PR6424	6.0mm (Extended Range)	≤ 1.0%
CON021/914-080	PR6424	8.0mm (Extended Range)	≤ 1.5%
CON021/914-100	PR6424	10.0mm (Extended Range)	≤ 2.0%
CON021/915-040	PR6425	4.0mm (Standard Range)	≤ 1.5%
CON021/915-060	PR6425	6.0mm (Extended Range)	≤ 2.0%
CON021/915-080	PR6425	8.0mm (Extended Range)	≤ 3.0%
CON021/915-100	PR6425	10.0mm (Extended Range)	≤ 4.0%
CON021/916-120	PR6426	12.0mm (Extended Range)	≤ 1.5%
CON021/916-160	PR6426	16.0mm (Extended Range)	≤ 2.0%
CON021/916-200	PR6426	20.0mm (Extended Range)	≤ 2.5%
CON021/916-240	PR6426	24.0mm (Extended Range)	≤ 3.5%

Emerson
Reliability Solutions
835 Innovation Drive
Knoxville, TN 37932 USA
+1 865 675 2400

www.emerson.com/ams

©2017, Emerson. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. All other marks are the property of their respective owners.

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.

Specifications Sheet
March 2013

CSI 6500 Machinery Health™ Monitor

Ordering Information, PR 6423

PR6423 Sleeve thread M10 x 1, sleeve length 55mm, adapter plug at 1 m, total cable length 30 m, open end cable

PR 6423	x	x	x	-	x	x	x
Sleeve Thread:							
M10 x 1	0						
3/8" – 24 –UNF – 2A	1			-			
Armored cable:							
Without		0		-			
With		1					
Sleeve length (+9.0 mm (.35 in) = total length):							
25 mm (.98 in)			0				
35 mm (1.38 in)			1				
45 mm (1.77 in)			2				
55 mm (2.17 in)			3				
65 mm (2.56 in)			4				
75 mm (2.95 in)			5				
85 mm (3.35 in)			6				
95 mm (3.74 in)			7				
105 mm (4.13 in)			8				
115 mm (4.53 in) (max. length)			9				
Adapter plug at 1 m (3.28 ft):							
With					0		
Without					1		
Total cable length:							
4 m (13.1 ft)						0	
5 m (16.4 ft)						1	
6 m (19.7 ft)						2	
8 m (26.2 ft)						3	
10 m (32.8 ft)						4	
Cable end:							
Lemo connector for converter							0
Blunt cut cable end for converter							1
PR 6423				-			

Emerson Process Management
Asset Optimization Division
835 Innovation Drive
Knoxville, TN 37932 USA
T (865) 675-2400
F (865) 218-1401

©2011, Emerson Process Management.

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability.
All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.

All rights reserved. Machinery Health, is a mark of one of the Emerson Process Management group of companies. The Emerson logo is a trademark and service mark of Emerson Electric Co. All other marks are the property of their respective owners.

Online Machinery Health Management powers PlantWeb through conditon monitoring of mechanical equipment to improve availability and performance.

EMERSON™
Process Management