SIEMENS

Data sheet 6DL1132-6BH00-0EH1

Siemens EcoTech

SIMATIC ET 200SP HA, digital output module, DQ 16X24VDC/0,5A HA, suitable for terminal block, H1, M1, color code CC02, channel diagnostics



Figure similar

General information	
Product type designation	DQ 16x24VDC/0.5A HA
Firmware version	V1.0
● FW update possible	Yes
Usable terminal block	type H1, M1, N0, H0, M0 (for details see the system manual)
Color code for module-specific color-coded label	CC02
Product function	
● I&M data	Yes; I&M0 to I&M3
Engineering with	
● SPPA-T3000 can be configured/integrated from version	V8.0
Operating mode	
● DQ	Yes
● DQ with energy-saving function	No
● PWM	No
● Oversampling	No
● MSO	No
Redundancy	
● Redundancy capability	Yes; With TB type M1
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	60 mA; without load
Current consumption, max.	70 mA; without load
Output voltage	
Rated value (DC)	24 V
Power loss	
Power loss, typ.	1.2 W; minimum - typ. specification not possible because load-dependent
Address area	
Address space per module	
● Address space per module, max.	8 byte; PII: 0 bytes, +2 bytes for QI information, +2 bytes of PROFINET status data; PIO: 2 bytes, +2 bytes of PROFINET status data
Digital outputs	

Subject to change without notice
© Copyright Siemens

Number of digital outputs	16
Current-sinking	No
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes; Ensure sufficient low-resistance cable routing to the sensor/actuator in order to attain the response threshold. Depending on the cable cross-section used, there may be constraints regarding the usable length of cable.
● Response threshold, typ.	0.7 A to 1.3 A (for IO redundancy up to max 2.6 A)
Open-circuit detection	Yes; 0.7 mA test current for wire-break diagnostics; this value is doubled in the case of IO redundancy
Overload protection	Yes
Limitation of inductive shutdown voltage to	L+ -(37 to 41V)
Controlling a digital input	Yes
Switching capacity of the outputs	
● with resistive load, max.	0.5 A
● on lamp load, max.	5 W
Load resistance range	
● lower limit	48 Ω
● upper limit	12 kΩ
Output current	
● for signal "1" rated value	0.5 A
● for signal "0" residual current, max.	0.7 mA; Test current for wire-break diagnostics; this value is doubled in the case of IO redundancy
Output delay with resistive load	
● "0" to "1", typ.	50 µs
● "1" to "0", typ.	100 µs
Parallel switching of two outputs	
● for uprating	No
● for redundant control of a load	Yes
Switching frequency	
● with resistive load, max.	100 Hz
● with inductive load, max.	2 Hz
● on lamp load, max.	10 Hz
Total current of the outputs	
● Current per channel, max.	0.5 A
● Current per module, max.	8 A
Total current of the outputs (per module)	
horizontal installation	
— up to 30 °C, max.	8 A
— up to 40 °C, max.	8 A
— up to 50 °C, max.	8 A
— up to 60 °C, max.	5.5 A
— up to 70 °C, max.	3 A
vertical installation	
— up to 30 °C, max.	8 A
— up to 40 °C, max.	6.33 A
— up to 50 °C, max.	4.67 A
— up to 60 °C, max.	3 A
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnoses	
● Monitoring the supply voltage	Yes
● Wire break	Yes; channel by channel
● Short-circuit to ground	Yes; channel by channel

Subject to change without notice
© Copyright Siemens

● Short-circuit to L+	Yes; channel by channel
● Group error	Yes
Diagnostics indication LED	
● MAINT LED	Yes; Yellow LED
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	Yes; red LED
● for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C
● horizontal installation, max.	70 °C
● vertical installation, min.	-40 °C
● vertical installation, max.	60 °C
Dimensions	
Width	22.5 mm
Height	115 mm
Depth	138 mm
Weights	
Weight, approx.	137 g

Classifications

	Version	Classification
eClass	16	27-24-26-04
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599

Approvals / Certificates

General Product Approval

Miscellaneous | Declaration of Conformity

General Product Approval | **For use in hazardous locations**

China RoHS | Miscellaneous | Manufacturer Declaration

For use in hazardous locations

Subject to change without notice
© Copyright Siemens

Declaration of Conformity

CCC

UL

ATEX

IECEx

Miscellaneous

Maritime application

ABS

BUREAU VERITAS

DNV

NK / Nippon Kaiji Kyokai

RINA

CCS (China Classification Society)

Environment

Siemens EcoTech

EPD

last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens