

Suzhou Lexsong Electromechanical Equipment Co.,Ltd.

LEXSONG

Contact: Kevin Song

Email: sales@lexsong-ev.com

Mobile Phone: +86 137 7167 0476

Website: www.lexsong-ev.com



Electric Industrial Truck



LS9040HF

Model	LS9040HF	LS9060HF
System Voltage	60V	60V
Battery	Lead Acid or Lithium 120AH	Lead Acid or Lithium 120AH
Motor	3KW AC	4KW AC
Controller	AC Controller	AC Controller
Overall Dimensions (mm)	2700X1380X1650	3480X1380X1650
Rear Cargo Box Dimensions (mm)	1000x1200x300	1700x1250x300
Max.speed	40km/h	40km/h
Max. Range (on flat road)	100km	80km
Climbing Ability	20%	20%
Turning Radius	4.5m	5m
Loading Weight	600kgs	800kgs



LS9060HF



LS9040HFX

Model	LS9040HFX	LS9060HFX
System Voltage	60V	60V
Battery	Lead Acid or Lithium 120AH	Lead Acid or Lithium 120AH
Motor	3KW AC	4KW AC
Controller	AC Controller	AC Controller
Overall Dimensions (mm)	2700X1380X1650	3480X1380X1650
Rear Cargo Box Dimensions (mm)	1000x1200x1050	1700x1250x1050
Max.speed	40km/h	40km/h
Max. Range (on flat road)	90km	70km
Climbing Ability	20%	20%
Turning Radius	4.5m	5m
Loading Weight	600kgs	800kgs



LS9060HFX

The rear box can be in normal steel box or aluminum box, can also be insulated box



Model	LS9040HFC	LS9060HFC
System Voltage	60V	60V
Battery	Lead Acid or Lithium 120AH	Lead Acid or Lithium 120AH
Motor	3KW AC	4KW AC
Controller	AC Controller	AC Controller
Overall Dimensions (mm)	2750X1380X1850	3600X1380X1850
Rear Cargo Box Dimensions (mm)	1000x1200x1050	1800x1250x1050
Max.speed	40km/h	40km/h
Max. Range (on flat road)	80km	60km
Climbing Ability	20%	20%
Turning Radius	4.5m	5.5m
Loading Weight	600kgs	800kgs



Rear box with refrigeration function

LS9060HFC



LS9040HFF



Model	LS9040HFF	LS9060HFF
System Voltage	60V	72V
Battery	Lead Acid or Lithium 120AH	Lead Acid or Lithium 120AH
Motor	3KW AC	6KW AC
Controller	AC Controller	AC Controller
Overall Dimensions (mm)	3000X1380X1850	3800X1400X1850
Rear Box Dimensions (mm)	1250x1200x1050	1800x1250x1050
Max.speed	40km/h	35km/h
Max. Range (on flat road)	80km	80km
Climbing Ability	20%	20%
Turning Radius	4.5m	5.5m
Loading Weight	400kgs	1500kgs



Rear box with water tank

LS9060HFF



LS6021H/LS6022H/LS6023H

Model	LS6021H	LS6022H	LS6023H
System Voltage	72V	72V	72V
Battery	100Ah Lithium 150Ah Lithium 200AH Lithium	150Ah Lithium 200AH Lithium	200AH Lithium
Motor	5KW/7.5KW AC	5KW/7.5KW AC	7.5KW AC
Controller	AC Controller	AC Controller	AC Controller
Overall Dimensions (mm)	4200X1500X1950	4200X1500X1950	4200X1500X1950
Max.speed	28km/h	28km/h	28km/h
Max. Range	50-100km	80-100km	100km
Climbing Ability	15%	15%	15%
Turning Radius	4.5m	4.5m	5m
Loading Weight	1000kgs	1500kgs	2000kgs





LS6021HT



LS6021HR

Model	LS6021HT	LS6021HR
System Voltage	72V	72V
Battery	150Ah Lithium 200AH Lithium	150Ah Lithium 200AH Lithium
Motor	5KW/7.5KW AC	5KW/7.5KW AC
Controller	AC Controller	AC Controller
Overall Dimensions (mm)	4200X1500X1950	4200X1500X1950
Max.speed	28km/h	28km/h
Max. Range	50-100km	80-100km
Climbing Ability	15%	15%
Turning Radius	4.5m	4.5m
Loading Weight	1000kgs	1500kgs
Rear Box	Thermal Box 2600*1400*1320mm	Refrigerator Box 2600*1400*1320mm

Temperature of the refrigerator box can be customized



LS6021HG

Model	LS6021HG	LS6021HC
System Voltage	72V	72V
Battery	150Ah Lithium 200AH Lithium	150Ah Lithium 200AH Lithium
Motor	5KW/7.5KW AC	5KW/7.5KW AC
Controller	AC Controller	AC Controller
Overall Dimensions (mm)	4200X1500X1950	4200X1500X1950
Max.speed	28km/h	28km/h
Max. Range	50-100km	80-100km
Climbing Ability	15%	15%
Turning Radius	4.5m	4.5m
Loading Weight	1000kgs	1000kgs



LS6021HC