



Zhangjiagang Weinuo Composite Materials Co., Ltd

No.80 Changjiang Mingzhu Road, Houcheng Street,
Zhangjiagang City, Jiangsu Province, China

24/02/2025

Technical Data Sheet

WNRD/T000A001R03

Weinuo Product code	WNQX800-24				
Description	Warp knitted fabric				
1. Client information					
Client name:	/				
Client description:	/				
Purchase specification:	/				
2. Technical information					
Ply sequence	Inside ← → Outside				
Fabric construction	0°	+ 45°	- 45°	90°	Stitching
Fiber code	SY-24K	SY-24K	SY-24K	SY-24K	—
Fiber filament count /tex	24,000	24,000	24,000	24,000	20
Fiber type	Carbon	Carbon	Carbon	Carbon	Polyester
Areal weight (g/m²)	200	200	200	200	10
Tolerance (g/m²)	± 6	± 6	± 6	± 6	±1
Roving manufacturer	ZF	ZF	ZF	ZF	—
Resin compatible	Epoxy compatible				
Gauge	5				
Stitch type	Chain				
Stitch length(mm)	2.50±0.01				
Total areal weight (g/m²)	800±3%				
Roll width (mm)	1270				
Roll length (m)	50				
Coloured pilot yarn	Customer's requirement.				
Label information	Supplier name, Supplier product name, Batch No., Day or week of product, Length, Width, Weight.				
Pallet information	Supplier name, Supplier product name, Batch No., Day or week of product, Length, Width, Weight.				
Remark	Angle tolerance is +/-2°.				
Grade Determination	A				
Inspection Conclusion	Inspector		Inspection Seal		
合格	许世铭		张江港伟诺复合材料股份有限公司 质检部 合格专用章		
	Inspector				
	方松				