

TECHNICAL DATA

REV	DESCRIPTION OF	ECN No.	BY	DATE	APPROVED
Rv01	N/A	N/A	J.Wang	2013/05/19	Karl Pan

Electrical data

Impedance 50Ω
Frequency range 0~14GHz
Working Voltage 1700V max
Withstand Voltage 2000V rms
VSWR
Straight ≤1.2(DC~11G)
Rigth Angle ≤1.3
Intermodulation (IM3) 2 x 20 W: ≤-159 dBC
Insulation resistance ≥10000MΩ

Mechanical data


Temperature range -55°C~+155°C
Durability(matings) >500

Material data

Piece Part	Base Material	Plating
Body	Brass	Tri-Metal
Center conductor	Phosphor Bronze	Silver plated
Coupling nut	Brass	Nickel plated
Gasket	Silicone Rubber	
Insulator	PTFE	

Interface Standards

DIN 47231 , IEC 60169-11



Part Name:

**L20 Male for 1/2
Super Flexible Cable**

W/T16D3,640,156

WORLDPEAK®

www.zjwdf.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4

SCALE: 4:1

SHEET: 1/1

REV: A

NOTES:
1.ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2.CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY